Package: cffr (via r-universe)

October 26, 2026

Title Generate Citation File Format ('CFF') Metadata

Version 1.4.2.9000

Description Citation File Format ('CFF') version 1.2.0 <doi:10.5281/zenodo.5171937> is a human- and machine-readable file format for software citation metadata. Core utilities generate, read, write and validate Citation File Format metadata for 'R' packages.

License GPL (>= 3)

URL https://docs.ropensci.org/cffr/, https://github.com/ropensci/cffr

BugReports https://github.com/ropensci/cffr/issues

Depends R (>= 4.1.0)

Imports cli (>= 2.0.0), desc (>= 1.3.0), jsonlite (>= 1.7.2), jsonvalidate (>= 1.1.0), tools, utils, yaml (>= 2.2.1)

Suggests bibtex (>= 0.5.0), knitr, lifecycle, quarto, rmarkdown, testthat (>= 3.3.0), usethis, withr

VignetteBuilder quarto

Config/Needs/website devtools

Config/roxygen2/markdown TRUE

Config/roxygen2/version 8.1.1

Config/testthat/edition 3

Config/testthat/parallel true

Encoding UTF-8

LazyData true

X-schema.org-applicationCategory Citation Management

X-schema.org-isPartOf https://ropensci.org

X-schema.org-keywords attribution, citation, credit, citation-files, cff, metadata, citation-file-format, cran, r, r-package, ropensci, rstats, r-cran

Config/pak/sysreqs libssl-dev libnode-dev

Repository https://ropensci.r-universe.dev

Date/Publication 2026-10-26 10:31:24 UTC

RemoteUrl https://github.com/ropensci/cffr

RemoteRef main

RemoteSha 44df2a2210db78c43278019ce94e56bf326ac40f

Contents

as_bibentry 2
as_cff 5
as_cff_person 7
cff 10
cff_create 12
cff_gha_update 14
cff_git_hook 15
cff_modify 16
cff_read 17
cff_read_bib_text 20
cff_schema 21
cff_validate 22
cff_write 23
cff_write_bib 25
cran_to_spdx 27

Index **29**

`as_bibentry` *Create* `bibentry` *objects from multiple sources*

Description

This function creates `bibentry` objects from multiple metadata sources (`cff` objects, `DESCRIPTION` files and other sources). The inverse transformation from a `bibentry` object to `cff_ref_lst` can be performed with the corresponding `as_cff.bibentry()` method.

With `toBibtex()`, you can convert `cff` objects to BibTeX markup on the fly. See **Examples**.

Usage

```
as_bibentry(x, ...)

## Default S3 method:
as_bibentry(x, ...)

## S3 method for class 'character'
as_bibentry(x, ..., what = c("preferred", "references", "all"))
```

```
## S3 method for class '`NULL`'
as_bibentry(x, ...)

## S3 method for class 'list'
as_bibentry(x, ...)

## S3 method for class 'cff'
as_bibentry(x, ..., what = c("preferred", "references", "all"))

## S3 method for class 'cff_ref_lst'
as_bibentry(x, ...)

## S3 method for class 'cff_ref'
as_bibentry(x, ...)
```

Arguments

x	The source used to generate the bibentry object with **cffr**. It can be: • A missing or NULL value, which retrieves the DESCRIPTION file from your in-development package. • An existing cff object created with cff(), cff_create() or as_cff(). • A path to a CITATION.cff file ("CITATION.cff"). • The name of an installed package ("jsonlite"). • A path to a DESCRIPTION file ("DESCRIPTION").
...	Additional arguments passed to or from methods.
what	Fields to extract from a full cff object. It can be: • preferred: Create a single entry with the main citation information of the package (key preferred-citation). • references: Extract all entries of the references key. • all: Extract both the preferred-citation and references keys. See vignette("r-cff", package = "cffr").

Details

An R bibentry object is the representation of a BibTeX entry. These objects can be converted to BibTeX markup with utils::toBibtex(), which creates an object of class Bibtex that can be printed and exported as a valid BibTeX entry.

as_bibentry() tries to map the information of the source x into a cff object and maps the metadata to BibTeX as described in vignette("bibtex-cff", package = "cffr").

Value

A bibentry object with one or more entries.

References

Patashnik O (1988). "BIBTEXing." https://osl.ugr.es/CTAN/biblio/bibtex/base/btxdoc.pdf.

Haines R, The Ruby Citation File Format Developers (2022). "Ruby CFF Library." doi:10.5281/zenodo.7294987. https://github.com/citation-file-format/ruby-cff.

Hernangómez D (2022). "BibTeX and CFF, a potential crosswalk." **cffr** vignette. https://docs.ropensci.org/cffr/articles/bibtex-cff.html.

See Also

- utils::bibentry() documents the bibentry class.
- vignette("r-cff", package = "cffr") explains how the metadata of a package is mapped to produce a cff object.
- vignette("bibtex-cff", package = "cffr") provides details about the internal mapping performed between cff objects and BibTeX markup, both cff to BibTeX and BibTeX to cff.
- utils::toBibtex() converts bibentry objects to BibTeX markup.

Work with BibTeX metadata: cff_read(), cff_read_bib_text(), cff_write_bib(), encoded_utf_to_latex()

Convert between R classes: as_cff(), as_cff_person(), cff_class

Examples

```
# From a `cff` object ----
cff_object <- cff()

cff_object

# A `bibentry` object.
bib <- as_bibentry(cff_object)

class(bib)

bib

# Print as BibTeX.
toBibtex(bib)

# The S3 method also supports this.
toBibtex(cff_object)

# Other sources ----
# From a CITATION.cff file.

path <- system.file("examples/CITATION_complete.cff", package = "cffr")
cff_file <- as_bibentry(path)

cff_file

# For an installed package with options.
```

```
installed_package <- as_bibentry("jsonvalidate", what = "all")

installed_package

# Use a DESCRIPTION file.
path2 <- system.file("examples/DESCRIPTION_gitlab", package = "cffr")
desc_file <- as_bibentry(path2)

toBibtex(desc_file)
```

`as_cff` *Coerce lists and citation objects to* `cff`

Description

`as_cff()` turns an existing list-like R object into a `cff` object, a list with class `cff` and the corresponding subclass when applicable.

`as_cff()` is an S3 generic, with methods for:

- `person` objects as produced by `utils::person()`.
- `bibentry` objects as produced by `utils::bibentry()`.
- `Bibtex` objects as produced by `utils::toBibtex()`.
- Default: Other inputs are first coerced with `base::as.list()`.

Usage

```
as_cff(x, ...)

## Default S3 method:
as_cff(x, ...)

## S3 method for class 'list'
as_cff(x, ...)

## S3 method for class 'person'
as_cff(x, ...)

## S3 method for class 'bibentry'
as_cff(x, ...)

## S3 method for class 'Bibtex'
as_cff(x, ...)

as.cff(x)
```

Arguments

x	A person, bibentry or other object that can be coerced to a list.
...	Additional arguments passed on to other methods.

Details

as.cff(x) is an alias for as_cff(x).

For as_cff.bibentry() and as_cff.Bibtex(), see vignette("bibtex-cff", package = "cffr") to understand how the mapping is performed.

as_cff_person() is preferred over as_cff.person() because it can handle character inputs such as "Davis, Jr., Sammy". For person objects, both functions behave similarly.

Value

- as_cff.person() returns an object with classes cff_pers_lst and cff.
- as_cff.bibentry() and as_cff.Bibtex() return an object with classes cff_ref_lst and cff.
- The remaining methods return a cff object. However, if x has a structure compatible with definitions.person, definitions.entity or definitions.reference, the object has the corresponding subclass.

Learn more about the **cffr** class system in cff_class.

See Also

- cff() creates a full cff object from scratch.
- cff_modify() modifies a cff object.
- cff_create() creates a cff object for an R package.
- cff_read() creates a cff object from an external file.

Convert between R classes: as_bibentry(), as_cff_person(), cff_class

Examples

```
# Convert a list to a `cff` object.
cffobj <- as_cff(list(
  "cff-version" = "1.2.0",
  title = "Manipulating files"
))

class(cffobj)

# Display the YAML representation.
cffobj

# `bibentry` method.
a_cit <- citation("cffr")[[1]]

a_cit
```

```
as_cff(a_cit)

# BibTeX method.
a_bib <- toBibtex(a_cit)

a_bib

as_cff(a_cit)
```

`as_cff_person` *Coerce* R *objects to* `cff_pers_lst` *objects*

Description

`as_cff_person()` turns an existing list-like R object into a `cff_pers_lst` object representing a list of `definitions.person` or `definitions.entity`, as defined in the following guide: Citation File Format schema guide.

`as_cff_person()` is an S3 generic, with methods for:

- `person`: Objects created with `utils::person()`.
- `character`: Strings with the definition for one or more authors, using the standard BibTeX notation (see Markey, 2009) and related formats, such as the output of `base::format()` for `person` objects (see `format.person()`).
- Default: Other inputs are first coerced with `base::as.character()`.

The inverse transformation (`cff_pers_lst` to `person`) can be performed with the methods `as.person.cff_pers()` and `as.person.cff_pers_lst()`.

Usage

```
as_cff_person(x, ...)

## Default S3 method:
as_cff_person(x, ...)

## S3 method for class 'person'
as_cff_person(x, ...)

## S3 method for class 'character'
as_cff_person(x, ...)
```

Arguments

`x`	Any R object.
`...`	Ignored by this method.

Details

`as_cff_person()` recognizes whether the input should be converted with the CFF reference for `definitions.person` or `definitions.entity`.

`as_cff_person()` uses a custom algorithm that parses names as explained in Section 11 of "Tame the BeaST" (Markey, 2009) (see also Decoret, 2007):

- `First von Last`.
- `von Last, First`.
- `von Last, Jr, First`.

Mapping is performed as follows:

- `First` is mapped to the CFF key `given-names`.
- `von` is mapped to the CFF key `name-particle`.
- `Last` is mapped to the CFF key `family-names`.
- `Jr` is mapped to the CFF key `name-suffix`.

For entities, the entire string is mapped to `name`. We recommend "protecting" entity names with `{}`:

```
# Avoid unprotected entity names.
entity <- "Elephant and Castle"
as_cff_person(entity)
- name: Elephant
- name: Castle

# Protect entity names with braces.
entity_protect <- "{Elephant and Castle}"
as_cff_person(entity_protect)
- name: Elephant and Castle
```

`as_cff_person()` attempts to extract as much information as possible. For `character` strings from `format.person()`, the email and ORCID are also extracted.

Value

An object with classes `cff_pers_lst` and `cff` representing `definitions.person` or `definitions.entity`, as defined in the following guide: Citation File Format schema guide. Each element of the `cff_pers_lst` object has classes `cff_pers` and `cff`.

References

Patashnik O (1988). "BIBTEXing." https://osl.ugr.es/CTAN/biblio/bibtex/base/btxdoc.pdf.

Markey N (2009). *Tame the BeaST: The B to X of BibTeX*. https://osl.ugr.es/CTAN/info/bibtex/tamethebeast/ttb_en.pdf.

Decoret X (2007). "A summary of BibTeX." https://maverick.inria.fr/~Xavier.Decoret/resources/xdkbibtex/bibtex_summary.html#names.

See Also

Examples in `vignette("cffr", package = "cffr")` and `utils::person()`. Learn more about the `cff_pers_lst` and `cff_pers` classes in cff_class.

Convert between R classes: `as_bibentry()`, `as_cff()`, `cff_class`

Examples

```
# Create a person object.
a_person <- person(
  given = "First", family = "Author",
  role = c("aut", "cre"),
  email = "first.last@example.com", comment = c(
    ORCID = "0000-0001-8457-4658",
    affiliation = "An affiliation"
  )
)

a_person

cff_person <- as_cff_person(a_person)

# Classes `cff_pers_lst` and `cff`.
class(cff_person)

# Each element has classes `cff_pers` and `cff`.
class(cff_person[[1]])

# Print.
cff_person

# Convert back to a `person` object with the S3 method.
as.person(cff_person)

# Coerce a string.
a_str <- paste0(
  "Julio Iglesias <fake@email.com> ",
  "(city: Miami, region: California, country: US)"
)
as_cff_person(a_str)

# Several people.
persons <- c(
  person("Clark", "Kent", comment = c(affiliation = "Daily Planet")),
  person("Lois", "Lane"), person("Oscorp Inc.")
)

a_cff <- as_cff_person(persons)

a_cff

# Print as BibTeX with the method.
toBibtex(a_cff)
```

```
# Or as a `person` object.
as.person(a_cff)

# Or use BibTeX style as input.

x <- "Frank Sinatra and Dean Martin and Davis, Jr., Sammy and Joey Bishop"

as_cff_person(x)

as_cff_person("Herbert von Karajan")

toBibtex(as_cff_person("Herbert von Karajan"))
```

`cff` *Create* `cff` *objects from direct inputs*

Description

A class and utility methods for reading, creating and storing CFF information. See cff_class to learn more about `cff` objects.

Usage

```
cff(path, ...)
```

Arguments

`path`	**[Deprecated]** `path` is no longer supported, use `cff_read_cff_citation()` instead.
`...`	Named arguments used to create a `cff` object. If no arguments are supplied (the default behavior), a minimal valid `cff` object is created.

Details

`cff()` converts `_` in the argument name to `-`. For example, `cff_version = "1.2.0"` is converted to `cff-version = "1.2.0"`.

Valid arguments are those specified on `cff_schema_keys()`:

- `cff-version`
- `message`
- `type`
- `license`
- `title`
- `version`
- `doi`

- identifiers
- abstract
- authors
- preferred-citation
- repository
- repository-artifact
- repository-code
- commit
- url
- date-released
- contact
- keywords
- references
- license-url

Value

A cff object. Under the hood, a cff object is a regular base::list() object with a special print method.

See Also

Core **cffr** workflow: cff_create(), cff_modify(), cff_validate(), cff_write()

Examples

```
# Blank `cff` object.
cff()

# Use custom parameters.
test <- cff(
  title = "Manipulating files",
  keywords = c("A", "new", "list", "of", "keywords"),
  authors = as_cff_person("New author")
)
test

# This would fail.
cff_validate(test)


# Modify with cff_create().
new <- cff_create(test, keys = list(
  "cff_version" = "1.2.0",
  message = "A blank file"
))
new
```

```
# This would pass.
cff_validate(new)
```

`cff_create` *Create a* `cff` *object from multiple sources*

Description

Create a full, possibly valid `cff` object from a given source. This object can be written to a `CITATION.cff` file with `cff_write()`. See **Examples**.

This function performs most metadata extraction and conversion in **cffr**.

Usage

```
cff_create(
  x,
  keys = list(),
  cff_version = "1.2.0",
  gh_keywords = TRUE,
  dependencies = TRUE,
  authors_roles = c("aut", "cre")
)
```

Arguments

`x`	The source used to generate the `cff` object. It can be: • A missing value, which retrieves the `DESCRIPTION` file from your in-development R package. • An existing `cff` object. • The name of an installed package (`"jsonlite"`). • A path to a `DESCRIPTION` file (`"./DESCRIPTION"`).
`keys`	A list of additional keys to add to the `cff` object. See `cff_modify()`.
`cff_version`	The Citation File Format schema version used for the generated metadata.
`gh_keywords`	A logical value. If `TRUE` and the package is hosted on GitHub, add the repository topics as keywords.
`dependencies`	A logical value. If `TRUE`, add installed package dependencies to the `references` CFF key. See **Details**.
`authors_roles`	Roles to be considered as authors of the package when generating the `CITATION.cff` file. See **Details**.

Details

If x is a path to a DESCRIPTION file or if inst/CITATION is not present in your package, **cffr** auto-generates a preferred-citation key using the information provided in that file.

When inst/CITATION is present, every field from the package's DESCRIPTION, including custom fields, is made available to that file through its meta object. If the file cannot be evaluated with those metadata, cff_create() does not retry with metadata from another package.

When dependencies = TRUE, cff_create() starts from the first reference returned by utils::citation() for each installed dependency. Citation fields such as title, abstract, authors and year are preserved. Each reference is adapted to the CFF software-reference type and enriched with the dependency scope and version constraint from the source DESCRIPTION, URLs and repository information from the installed dependency's DESCRIPTION and the canonical CRAN DOI only when the dependency is available from CRAN. A release date, when present, determines the year, with the citation year retained otherwise.

By default, only persons whose role in the DESCRIPTION file of the package is author ("aut") or maintainer ("cre") are considered package authors. The default setting can be controlled with the authors_roles argument. See **Details** on utils::person() for additional information about person roles.

Value

A cff object.

See Also

Citation File Format schema guide.

- vignette("cffr", package = "cffr") shows an introduction to manipulating cff objects.
- vignette("r-cff", package = "cffr") provides details about how the metadata of a package is mapped to produce a cff object.

Core **cffr** workflow: cff(), cff_modify(), cff_validate(), cff_write()

Examples

```
# Installed package.
cff_create("jsonlite")

# Demo file.
demo_file <- system.file("examples/DESCRIPTION_basic", package = "cffr")
cff_create(demo_file)

# Add additional keys.

newkeys <- list(
  message = "This overwrites keys",
  abstract = "New abstract",
  keywords = c("A", "new", "list", "of", "keywords"),
  authors = as_cff_person("New author")
)
```

```
cff_create(demo_file, keys = newkeys)

# Update a key in a list, such as authors or contacts.
# Add a new contact.

old <- cff_create(demo_file)

new_contact <- append(
  old$contact,
  as_cff_person(person(
    given = "I am",
    family = "New Contact"
  ))
)

cff_create(demo_file, keys = list("contact" = new_contact))
```

`cff_gha_update` *Install a* R*hrefhttps://CRAN.R-project.org/package=cffr***cffr** *GitHub Actions workflow*

Description

This function installs a GitHub Actions workflow in your repository. The workflow updates your `CITATION.cff` file when any of these events occur:

- You publish a new release of the package.
- Your `DESCRIPTION` or `inst/CITATION` file is modified.
- You run the workflow manually.

Usage

```
cff_gha_update(path = ".", overwrite = FALSE)
```

Arguments

`path`	Project root directory.
`overwrite`	A logical value. If `TRUE`, overwrite an existing workflow.

Details

Workflow triggers can be modified. See Events that trigger workflows.

Value

Invisibly returns `NULL`. This function is called for its side effects.

See Also

Keep 'CITATION.cff' up to date: cff_git_hook

Examples

```
## Not run:
cff_gha_update()

## End(Not run)
```

---

cff_git_hook *Use a Git pre-commit hook* **[Experimental]**

Description

Install a pre-commit hook that reminds you to update your CITATION.cff file. This is a wrapper around usethis::use_git_hook().

Usage

```
cff_git_hook_install()

cff_git_hook_remove()
```

Details

This function installs a pre-commit hook using usethis::use_git_hook().

A pre-commit hook is a script that identifies simple issues before submission to code review. This pre-commit hook warns you if any of the following conditions are met:

- You included your DESCRIPTION or inst/CITATION file in a commit but did not include your CITATION.cff file and the CITATION.cff file is "older" than your DESCRIPTION or inst/CITATION file.
- You updated your CITATION.cff file but did not include it in your commit.

Value

Invisibly returns NULL. This function is called for its side effects.

A word of caution

The pre-commit hook may prevent you from committing if you are not updating your CITATION.cff file. However, the detection mechanism is not perfect and may be triggered even if you have attempted to update your CITATION.cff file.

This typically occurs when you have updated your DESCRIPTION or inst/CITATION files but those changes do not affect your CITATION.cff file, for example, when you add new dependencies.

In those cases, you can override the check by running `git commit --no-verify` in the terminal.

If you are using **RStudio**, you can also run this command from an R script by selecting that line and sending it to the terminal with:

- Windows and Linux: `Ctrl+Alt+Enter`.
- macOS: `Cmd+Option+Return`.

Removing the Git pre-commit hook

You can remove the pre-commit hook using `cff_git_hook_remove()`.

See Also

- `usethis::use_git_hook()`, which is the underlying function used by `cff_git_hook_install()`.
- `usethis::use_git()` and related functions of **usethis** for using Git with R packages.

Keep 'CITATION.cff' up to date: `cff_gha_update()`

Examples

```
## Not run:
cff_git_hook_install()

## End(Not run)
```

---

cff_modify *Modify a cff object*

Description

Add new keys to a `cff` object or modify existing ones.

Usage

```
cff_modify(x, ...)
```

Arguments

x	A `cff` object.
...	Named arguments used to modify `x`. See also the `...` argument in `cff()`.

Details

Keys provided in `...` override the corresponding key in `x`.

You can add additional keys not detected by `cff_create()` using the `keys` argument. A list of valid keys can be retrieved with `cff_schema_keys()`. See the following guide for additional details: Citation File Format schema guide.

Value

A cff object.

See Also

This function is a wrapper of utils::modifyList().

Core **cffr** workflow: cff(), cff_create(), cff_validate(), cff_write()

Examples

```
x <- cff()
x

cff_validate(x)

x_mod <- cff_modify(x,
  contact = as_cff_person("A contact"),
  message = "This overwrites keys",
  title = "New Title",
  abstract = "New abstract",
  doi = "10.21105/joss.03900"
)

x_mod

cff_validate(x_mod)
```

---

cff_read *Read an external file as a cff object*

Description

Read files and convert them to cff objects. Supported files are:

- CITATION.cff files.
- DESCRIPTION files.
- R citation files (usually located in inst/CITATION).
- BibTeX files (with extension *.bib).

cff_read() attempts to guess the type of file provided in path. However, we provide aliases for each specific file type:

- cff_read_cff_citation(), which uses yaml::read_yaml().
- cff_read_description(), which uses desc::desc().
- cff_read_citation(), which uses utils::readCitationFile().
- cff_read_bib(), which requires **bibtex** (>= 0.5.0) and uses bibtex::read.bib().

Usage

```
cff_read(path, ...)

cff_read_cff_citation(path, ...)

cff_read_description(
  path,
  cff_version = "1.2.0",
  gh_keywords = TRUE,
  authors_roles = c("aut", "cre"),
  ...
)

cff_read_citation(path, meta = NULL, ...)

cff_read_bib(path, encoding = "UTF-8", ...)
```

Arguments

path	A path to a file.
...	Arguments passed to other functions, for example to yaml::read_yaml() or bibtex::read.bib().
cff_version	The Citation File Format schema version used for the generated metadata.
gh_keywords	A logical value. If TRUE and the package is hosted on GitHub, add the repository topics as keywords.
authors_roles	Roles to be considered as authors of the package when generating the CITATION.cff file. See **Details**.
meta	A package metadata object as obtained by utils::packageDescription() or NULL (the default). See **Details**.
encoding	Encoding to be assumed for path. See base::readLines().

Details

For details of cff_read_description(), see cff_create().

The meta object:

Section 1.9, "CITATION files", of *Writing R Extensions* (R Core Team 2026) specifies how to create dynamic CITATION files using a meta object. cff_read_citation() makes every field supplied in meta, including custom DESCRIPTION fields, available to the CITATION file. When cff_create() reads a package CITATION file, it constructs meta from all fields in that package's DESCRIPTION. With meta = NULL, only default encoding metadata is supplied. If the file cannot be evaluated with those metadata, cff_read_citation() returns NULL rather than substituting metadata from another package.

Value

- cff_read_cff_citation() and cff_read_description() return a cff object.

- `cff_read_bib()` returns an object with classes `cff_ref_lst` and `cff` representing `definitions.reference`, as defined in the following guide: Citation File Format schema guide.
- `cff_read_citation()` returns the same classes as `cff_read_bib()` or `NULL` when the file cannot be evaluated.

Learn more about the **cffr** class system in cff_class.

References

R Core Team (2026). *Writing R Extensions*. https://cran.r-project.org/doc/manuals/r-release/R-exts.html.

Hernangómez D (2022). "BibTeX and CFF, a potential crosswalk." **cffr** vignette. https://docs.ropensci.org/cffr/articles/bibtex-cff.html.

See Also

The underlying functions used for reading external files:

- `yaml::read_yaml()` for `CITATION.cff` files.
- `desc::desc()` for `DESCRIPTION` files.
- `utils::readCitationFile()` for R citation files.
- `bibtex::read.bib()` for BibTeX files (extension `*.bib`).

Read external citation metadata: `cff_read_bib_text()`

Work with BibTeX metadata: `as_bibentry()`, `cff_read_bib_text()`, `cff_write_bib()`, `encoded_utf_to_latex()`

Examples

```
# Create a `cff` object from a `CITATION.cff` file.
from_cff_file <- cff_read(system.file("examples/CITATION_basic.cff",
  package = "cffr"
))

head(from_cff_file, 7)

# Create a `cff` object from DESCRIPTION.
from_desc <- cff_read(system.file("examples/DESCRIPTION_basic",
  package = "cffr"
))

from_desc

# Create a `cff` object from BibTeX.
if (requireNamespace("bibtex", quietly = TRUE)) {
  from_bib <- cff_read(system.file("examples/example.bib",
    package = "cffr"
  ))

  # First item only.
  from_bib[[1]]
}
```

```
# Create a `cff` object from CITATION.
from_citation <- cff_read(system.file("CITATION", package = "cffr"))

# First item only.
from_citation[[1]]
```

`cff_read_bib_text` *Read BibTeX markup as a* `cff_ref_lst` *object*

Description

Convert one or more complete BibTeX entries supplied as a `character` vector into a `cff_ref_lst` object.

Usage

```
cff_read_bib_text(x, encoding = "UTF-8", ...)
```

Arguments

`x`	A `character` vector with one or more complete BibTeX entries.
`encoding`	Encoding to be assumed for `x`. See `base::readLines()`.
`...`	Arguments passed to `cff_read_bib()`.

Details

This function writes `x` to a temporary `*.bib` file and reads it using `cff_read_bib()`.

This function requires **bibtex** (>= 0.5.0) and uses `bibtex::read.bib()` for parsing.

Value

An object with classes `cff_ref_lst` and `cff` representing `definitions.reference`, as defined in the following guide: Citation File Format schema guide. Each element of the `cff_ref_lst` object has classes `cff_ref` and `cff`.

See Also

`cff_read_bib()` for reading `*.bib` files.

Work with BibTeX metadata: `as_bibentry()`, `cff_read()`, `cff_write_bib()`, `encoded_utf_to_latex()`

Read external citation metadata: `cff_read()`

Examples

```
if (requireNamespace("bibtex", quietly = TRUE)) {
  x <- c(
    "@book{einstein1921,
      title        = {Relativity: The Special and the General Theory},
      author       = {Einstein, Albert},
      year         = 1920,
      publisher    = {Henry Holt and Company},
      address      = {London, United Kingdom},
      isbn         = 9781587340925
  }",
    "@misc{misc-full,
      title        = {Handing out random pamphlets in airports},
      author       = {Joe-Bob Missilany},
      year         = 1984,
      month        = oct,
      note         = {This is a full MISC entry},
      howpublished = {Handed out at O'Hare}
  }"
  )

  cff_read_bib_text(x)
}
```

---

cff_schema *Inspect CFF schema values*

Description

Helper functions with valid values for different keys and definition fields. See the following guide: Citation File Format schema guide.

- `cff_schema_keys()` provides the valid high-level keys of the Citation File Format.
- `cff_schema_keys_license()` provides valid SPDX license identifiers for the `CITATION.cff` file.
- `cff_schema_definitions_person()` and `cff_schema_definitions_entity()` return the valid fields to include when defining a person or entity.
- `cff_schema_definitions_refs()` provides the valid keys to use in the `preferred-citation` and `references` keys.

Usage

```
cff_schema_keys(sorted = FALSE)

cff_schema_keys_license()

cff_schema_definitions_person()
```

```
cff_schema_definitions_entity()

cff_schema_definitions_refs()
```

Arguments

sorted	A logical value. If TRUE, arrange the keys alphabetically.

Value

A character vector with the names of valid keys for Citation File Format version 1.2.0.

Source

Citation File Format schema guide.

Examples

```
cff_schema_keys(sorted = TRUE)
# Valid license keys.
head(cff_schema_keys_license(), 20)
cff_schema_definitions_person()
cff_schema_definitions_entity()
cff_schema_definitions_refs()
```

---

cff_validate *Validate a* CITATION.cff *file or a* cff *object*

Description

Validate a CITATION.cff file or a cff object using the corresponding validation schema.

Usage

```
cff_validate(x = "CITATION.cff", verbose = TRUE)
```

Arguments

x	A full cff object created with cff_create() or the path to a CITATION.cff file to be validated. A *.cff file is read with cff_read_cff_citation().
verbose	A logical value. If TRUE, the function displays informative messages.

Value

Invisibly returns a logical value indicating the validation result. On error, the result has an "errors" attribute with the error summary. If verbose is TRUE, the function also displays the result. See **Examples** and base::attr().

See Also

jsonvalidate::json_validate(), which is the function that performs the validation.

Citation File Format schema guide.

Core **cffr** workflow: cff(), cff_create(), cff_modify(), cff_write()

Examples

```
# Full `.cff` example.
cff_validate(system.file("examples/CITATION_complete.cff", package = "cffr"))

# Validate a `cff` object.
cffr <- cff_create("jsonlite")
class(cffr)
cff_validate(cffr)


# `.cff` with errors.
err_f <- system.file("examples/CITATION_error.cff", package = "cffr")
# You can manipulate the errors as a data frame.
res <- try(cff_validate(err_f))

isTRUE(res)
isFALSE(res)

# Detailed results.
df_errors <- attr(res, "errors")

df_errors[, c("field", "message")]

# An R citation file is not a `.cff` file, so it throws an error.
try(cff_validate(system.file("CITATION", package = "cffr")))
```

---

cff_write *Write a* CITATION.cff *file*

Description

cff_write() is the primary workflow for package development.

This function writes a CITATION.cff file for a given package. It wraps cff_create() to create the cff object, then writes it to a YAML-formatted file in one command.

Usage

```
cff_write(
  x,
  outfile = "CITATION.cff",
  keys = list(),
  cff_version = "1.2.0",
```

```
  gh_keywords = TRUE,
  r_citation = FALSE,
  dependencies = TRUE,
  validate = TRUE,
  verbose = TRUE,
  authors_roles = c("aut", "cre"),
  encoding = "UTF-8"
)
```

Arguments

x	The source used to generate the cff object. It can be: • A missing value, which retrieves the DESCRIPTION file from your in-development R package. • An existing cff object. • The name of an installed package ("jsonlite"). • A path to a DESCRIPTION file ("./DESCRIPTION").
outfile	The name and path of the CITATION.cff to be created. Relative paths are resolved from the current working directory, independently of the source specified in x.
keys	A list of additional keys to add to the cff object. See cff_modify().
cff_version	The Citation File Format schema version used for the generated metadata.
gh_keywords	A logical value. If TRUE and the package is hosted on GitHub, add the repository topics as keywords.
r_citation	A logical value. If TRUE, the R package citation (inst/CITATION) is created or updated relative to the current working directory. **No backup copy is created**. For more control, use cff_write_citation().
dependencies	A logical value. If TRUE, add installed package dependencies to the references CFF key. See **Details**.
validate	A logical value. If TRUE, validate the new file with cff_validate().
verbose	A logical value. If TRUE, the function displays informative messages.
authors_roles	Roles to be considered as authors of the package when generating the CITATION.cff file. See **Details**.
encoding	The name of the encoding to be assumed. Default is "UTF-8", but it can be any other value accepted by base::iconv(), such as "ASCII//TRANSLIT".

Details

For details of authors_roles and dependency extraction, see cff_create().

The x argument identifies the metadata source. It does not determine the output directory. This allows you to create a CITATION.cff file from a package or file located outside the current working directory.

When creating and writing a CITATION.cff file for a package in the current working directory, this function adds the pattern "^CITATION\.cff$" to the local .Rbuildignore file.

Value

Invisibly returns the generated `cff` object. This function is called primarily for its side effect of writing a `CITATION.cff` file.

See Also

Citation File Format schema guide.

Core **cffr** workflow: `cff()`, `cff_create()`, `cff_modify()`, `cff_validate()`

Write citation metadata files: `cff_write_bib()`

Examples

```
tmpfile <- tempfile(fileext = ".cff")
cff_obj <- cff_write("jsonlite", outfile = tmpfile)

cff_obj

# Force cleanup.
file.remove(tmpfile)
```

---

cff_write_bib *Export R objects to multiple file types*

Description

Export R objects representing citations to specific file formats:

- `cff_write_bib()` creates a `.bib` file.
- `cff_write_citation()` creates an R citation file as described in Section 1.9 of *Writing R Extensions* (R Core Team 2026).

Usage

```
cff_write_bib(
  x,
  file = tempfile(fileext = ".bib"),
  append = FALSE,
  verbose = TRUE,
  ascii = FALSE,
  ...
)

cff_write_citation(
  x,
  file = tempfile("CITATION_"),
  append = FALSE,
```

```
  verbose = TRUE,
  ...
)
```

Arguments

x	A bibentry or a cff object.
file	Name of the file to be created. If NULL, the lines are displayed instead.
append	A logical value. If TRUE, append entries to an existing file.
verbose	A logical value. If TRUE, display informative messages.
ascii	A logical value. If TRUE, write entries using ASCII characters only.
...	Arguments passed on to as_bibentry.cff, as_bibentry.cff_ref, as_bibentry.cff_ref_lst
	what Fields to extract from a full cff object. It can be: • preferred: Create a single entry with the main citation information of the package (key preferred-citation). • references: Extract all entries of the references key. • all: Extract both the preferred-citation and references keys. See vignette("r-cff", package = "cffr").

Details

When x is a cff object, it is converted to BibTeX using toBibtex.cff().

For security reasons, if the file already exists, the function creates a backup copy in the same directory.

Value

Invisibly returns NULL. This function is called for its side effect of writing a file or displaying its contents.

References

R Core Team (2026). *Writing R Extensions*. https://cran.r-project.org/doc/manuals/r-release/R-exts.html.

See Also

vignette("bibtex-cff", package = "cffr"), knitr::write_bib() and the following packages: **bibtex**, **RefManageR** and **rbibutils**.

Work with BibTeX metadata: as_bibentry(), cff_read(), cff_read_bib_text(), encoded_utf_to_latex()

Write citation metadata files: cff_write()

Examples

```
bib <- bibentry("Misc",
  title = "My title",
  author = "Fran Pérez"
)

my_temp_bib <- tempfile(fileext = ".bib")

cff_write_bib(bib, file = my_temp_bib)

cat(readLines(my_temp_bib), sep = "\n")

cff_write_bib(bib, file = my_temp_bib, ascii = TRUE, append = TRUE)

cat(readLines(my_temp_bib), sep = "\n")
# Create an R citation file.
# Use a system file.
f <- system.file("examples/preferred-citation-book.cff", package = "cffr")
a_cff <- cff_read(f)

out <- file.path(tempdir(), "CITATION")
cff_write_citation(a_cff, file = out)

# Check by reading with a meta object.
meta <- packageDescription("cffr")
meta$Encoding <- "UTF-8"

utils::readCitationFile(out, meta)
```

---

cran_to_spdx *Mapping between* License *fields and SPDX*

Description

A dataset containing the mapping between the License strings observed in CRAN packages and their approximate match in the SPDX License List.

Format

A data frame with 87 rows and two variables:

LICENSE A valid License string on CRAN.

SPDX A valid SPDX license identifier.

Source

https://spdx.org/licenses/.

See Also

Writing R Extensions, Licensing section.

Examples

```
data("cran_to_spdx")

head(cran_to_spdx, 20)
```

Index

∗ **bibtex**
  as_bibentry, 2
  cff_read, 17
  cff_read_bib_text, 20
  cff_write_bib, 25
∗ **conversions**
  as_bibentry, 2
  as_cff, 5
  as_cff_person, 7
∗ **core**
  cff, 10
  cff_create, 12
  cff_modify, 16
  cff_validate, 22
  cff_write, 23
∗ **datasets**
  cran_to_spdx, 27
∗ **git**
  cff_gha_update, 14
  cff_git_hook, 15
∗ **reading**
  cff_read, 17
  cff_read_bib_text, 20
∗ **schemas**
  cff_schema, 21
∗ **writing**
  cff_write, 23
  cff_write_bib, 25

as.cff *(*as_cff*)*, 5
as.person.cff_pers(), *7*
as.person.cff_pers_lst(), *7*
as_bibentry, 2
as_bibentry(), *6*, *9*, *19*, *20*, *26*
as_bibentry.cff, *26*
as_bibentry.cff_ref, *26*
as_bibentry.cff_ref_lst, *26*
as_cff, 5
as_cff(), *3*, *4*, *9*
as_cff.bibentry(), *2*
as_cff_person, 7
as_cff_person(), *4*, *6*

base::as.character(), *7*
base::as.list(), *5*
base::attr(), *22*
base::format(), *7*
base::iconv(), *24*
base::list(), *11*
base::readLines(), *18*, *20*
bibentry, *2*, *3*, *26*
bibtex::read.bib(), *17–20*

cff, *2*, *3*, *5*, *6*, *8*, 10, *10–13*, *16–20*, *22–26*
cff(), *3*, *6*, *13*, *16*, *17*, *23*, *25*
cff_class, *4*, *6*, *9*, *10*, *19*
cff_create, 12
cff_create(), *3*, *6*, *11*, *16–18*, *22–25*
cff_gha_update, 14
cff_gha_update(), *16*
cff_git_hook, 15, *15*
cff_git_hook_install *(*cff_git_hook*)*, 15
cff_git_hook_remove *(*cff_git_hook*)*, 15
cff_modify, 16
cff_modify(), *6*, *11–13*, *23–25*
cff_pers, *8*
cff_pers_lst, *6–8*
cff_read, 17
cff_read(), *4*, *6*, *17*, *20*, *26*
cff_read_bib *(*cff_read*)*, 17
cff_read_bib(), *17*, *20*
cff_read_bib_text, 20
cff_read_bib_text(), *4*, *19*, *26*
cff_read_cff_citation *(*cff_read*)*, 17
cff_read_cff_citation(), *10*, *17*, *22*
cff_read_citation *(*cff_read*)*, 17
cff_read_citation(), *17*, *18*
cff_read_description *(*cff_read*)*, 17
cff_read_description(), *17*
cff_ref, *20*

cff_ref_lst, 2, 6, 19, 20
cff_schema, 21
cff_schema_definitions_entity (cff_schema), 21
cff_schema_definitions_entity(), 21
cff_schema_definitions_person (cff_schema), 21
cff_schema_definitions_person(), 21
cff_schema_definitions_refs (cff_schema), 21
cff_schema_definitions_refs(), 21
cff_schema_keys (cff_schema), 21
cff_schema_keys(), 10, 16, 21
cff_schema_keys_license (cff_schema), 21
cff_schema_keys_license(), 21
cff_validate, 22
cff_validate(), 11, 13, 17, 24, 25
cff_write, 23
cff_write(), 11–13, 17, 23, 26
cff_write_bib, 25
cff_write_bib(), 4, 19, 20, 25
cff_write_citation (cff_write_bib), 25
cff_write_citation(), 24, 25
character, 22
cran_to_spdx, 27

data frame, 27
desc::desc(), 17, 19

encoded_utf_to_latex(), 4, 19, 20, 26

format.person(), 7, 8

jsonvalidate::json_validate(), 23

knitr::write_bib(), 26

logical, 22

print, 11

subclass, 5

toBibtex(), 2
toBibtex.cff(), 26

usethis::use_git(), 16
usethis::use_git_hook(), 15, 16
utils::bibentry(), 4, 5
utils::citation(), 13
utils::modifyList(), 17
utils::packageDescription(), 18
utils::person(), 5, 7, 9, 13
utils::readCitationFile(), 17, 19
utils::toBibtex(), 3–5

yaml::read_yaml(), 17–19