

Package: emodnet.wfs (via r-universe)

January 28, 2025

Title Access 'EMODnet' Web Feature Service data through R

Version 2.0.2.9000

Description Access and interrogate 'EMODnet' (European Marine Observation and Data Network) Web Feature Service data through R.

License MIT + file LICENSE

URL <https://docs.ropensci.org/emodnet.wfs/>,
<https://github.com/EMODnet/emodnet.wfs>

BugReports <https://github.com/EMODnet/emodnet.wfs/issues>

Depends R (>= 3.6.0)

Imports checkmate, cli, dplyr, lifecycle, magrittr, memoise, ows4R (>= 0.4.1), purrr, rlang, sf, tibble, utils, whoami

Suggests covr, htptest, knitr, mapview, readr, rmarkdown, testthat (>= 3.1.2), testthis, withr

VignetteBuilder knitr

Remotes eblondel/ows4R

Config/Needs/readme rerddap

Config/Needs/website webshot

Config/testthat/edition 3

Config/testthat/parallel true

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

SystemRequirements C++11, GDAL (>= 2.0.1), GEOS (>= 3.4.0), PROJ (>= 4.8.0)

Config/pak/sysreqs libgdal-dev gdal-bin libgeos-dev libsecret-1-dev libxml2-dev libssl-dev libproj-dev libssqlite3-dev libx11-dev

Repository <https://ropensci.r-universe.dev>

RemoteUrl <https://github.com/EMODnet/emodnet.wfs>

RemoteRef main

RemoteSha 194274ba8ade6b52029e445ba48070229e37f856

Contents

<code>emodnet_get_layers</code>	2
<code>emodnet_get_layer_info</code>	4
<code>emodnet_init_wfs_client</code>	5
<code>emodnet_wfs</code>	6
<code>layer_attributes_get_names</code>	7
<code>layer_attributes_summarise</code>	8
<code>layer_attributes_tbl</code>	9
<code>layer_attribute_descriptions</code>	10
<code>layer_attribute_inspect</code>	11

Index

[13](#)

`emodnet_get_layers` *Get EMODnet WFS datasets (layers)*

Description

Performs an WFS getFeature request for layers from a `wfs` object or specified EMODnet Service. Filtering of layer features can also be handled via ECQL language filters.

Usage

```
emodnet_get_layers(
  wfs = NULL,
  service = NULL,
  service_version = NULL,
  layers,
  crs = NULL,
  cql_filter = NULL,
  simplify = FALSE,
  reduce_layers = deprecated(),
  ...
)
```

Arguments

<code>wfs</code>	A <code>WFSCClient R6</code> object with methods for interfacing an OGC Web Feature Service. From <code>emodnet_init_wfs_client()</code> .
<code>service</code>	the EMODnet OGC WFS service name. For available services, see <code>emodnet_wfs()</code> .
<code>service_version</code>	[Deprecated] the WFS service version. Now always "2.0.0".

layers	a character vector of layer names. To get info on layers, including <code>layer_name</code> use <code>emodnet_get_wfs_info()</code> .
crs	integer. EPSG code for the output crs. If NULL (default), layers are returned with original crs.
cql_filter	character. Features returned can be filtered using valid Extended Common Query Language (EQL) filtering statements (https://docs.geoserver.org/stable/en/user/filter/ecql_reference.html). Should be one of: <ul style="list-style-type: none"> • character string or character vector of length 1. Filter will be recycled across all layers requested. • character vector of length equal to the length of layers. Filter will be matched to layers sequentially. Elements containing NA are ignored • named character vector. Each filter will be applied to the layer corresponding to the filter name. Filters with names that do not correspond to any layers are ignored. Layers without corresponding filters are returned whole.
simplify	whether to reduce output layers to a single sf object. This only works if the column names are the same.
reduce_layers	[Deprecated] use <code>simplify</code> .
...	additional vendor parameter arguments passed to <code>ows4R::GetFeature()</code> . For example, including <code>count = 1</code> returns the first available feature. Or <code>outputFormat = "CSV"</code> (or <code>outputFormat = "JSON"</code>) might help downloading bigger datasets.

Value

If `simplify = FALSE` (default), a list of sf objects, one element for each layer. Any layers for which download was unsuccessful will be NULL. If `simplify = TRUE`, all layers are reduced (if possible: if all column names are the same) to a single sf containing data for all layers. NULL layers are ignored. `simplify = TRUE` can also be used to return an sf out of a single layer request instead of a list of length 1.

Big downloads

If a layer is really big (like "abiotic_observations" of the "biology_occurrence_data" service), you might consider a combination of these ideas:

- using `outputFormat = "CSV"`;
- filtering using `cql_filters` or `bounding boxes` (possibly splitting the area of interests into several requests);
- Using [EMODnet's download toolbox](#).

Examples

```
# Layers as character vector
emodnet_get_layers(
  service = "biology",
  layers = c("mediseh_zostera_m_pnt", "mediseh_posidonia_nodata")
)
```

```

# Usage of cql_filter
emodnet_get_layers(
  service = "biology",
  layers = "mediseh_zostera_m_pnt",
  cql_filter = "country = 'Francia'"
)
# Usage of vendor parameter
emodnet_get_layers(
  service = "biology",
  layers = "mediseh_zostera_m_pnt",
  count = 1
)

# Usage of csv output
data <- emodnet_get_layers(
  service = "biology_occurrence_data",
  layers = "abiotic_observations",
  outputFormat = "CSV"
)
str(data[["abiotic_observations"]])

```

emodnet_get_layer_info

Metadata about data available from the different services: data (layers) from a data source (service), metadata on layers from a service, metadata on layers from all services.

Description

Get WFS available layer information

Usage

```

emodnet_get_layer_info(wfs, layers)

emodnet_get_wfs_info(wfs = NULL, service = NULL, service_version = NULL)

emodnet_get_all_wfs_info()

```

Arguments

wfs	A WFSClient R6 object with methods for interfacing an OGC Web Feature Service. From emodnet_init_wfs_client() .
layers	a character vector of layer names. To get info on layers, including <code>layer_name</code> use emodnet_get_wfs_info() .
service	the EMODnet OGC WFS service name. For available services, see emodnet_wfs() .
service_version	[Deprecated] the WFS service version. Now always "2.0.0".

Details

To minimize the number of requests sent to webservices, these functions use `memoise` to cache results inside the active R session. To clear the cache, re-start R or run `memoise::forget(emodnet_get_wfs_info)/memoise::forget(emodnet_get_layer_info)`.

Value

a tibble containing metadata on each layer available from the service.

Functions

- `emodnet_get_layer_info()`: Get metadata for specific layers. Requires a `wfs` object as input.
- `emodnet_get_wfs_info()`: Get info on all layers from an EMODnet WFS service.
- `emodnet_get_all_wfs_info()`: Get metadata on all layers and all available services from server.

Examples

```
emodnet_get_wfs_info(service = "bathymetry")
# Query a wfs object
wfs_bio <- emodnet_init_wfs_client("biology")
emodnet_get_wfs_info(wfs_bio)
# Get info for specific layers from wfs object
layers <- c("mediseh_zostera_m_pnt", "mediseh_posidonia_nodata")
emodnet_get_layer_info(wfs = wfs_bio, layers = layers)
```

emodnet_init_wfs_client

Connect to a data source (service)

Description

Initialise an EMODnet WFS client

Usage

```
emodnet_init_wfs_client(service, service_version = NULL, logger = NULL)
```

Arguments

<code>service</code>	the EMODnet OGC WFS service name. For available services, see emodnet_wfs() .
<code>service_version</code>	[Deprecated] the WFS service version. Now always "2.0.0".
<code>logger</code>	the logger. Either <code>NULL</code> (no logging info), <code>"INFO"</code> (log about ows4R requests) or <code>"DEBUG"</code> (including curl details).

Value

An [ows4R::WFSClient](#) R6 object with methods for interfacing an OGC Web Feature Service.

See Also

[WFSClient](#) in package [ows4R](#).

Examples

```
wfs <- emodnet_init_wfs_client(service = "bathymetry")
```

emodnet_wfs

Which data sources (services) are available?

Description

Available EMODnet Web Feature Services

Usage

```
emodnet_wfs()
```

Format

emodnet_wfs:

emodnet_thematic.lot EMODnet disciplinary themes - bathymetry, biology, chemistry, geology, human activities, physics and seabed habitats

service_name Name of the specific service. Use in [emodnet_init_wfs_client](#).

service_url [Web Feature Service \(WFS\)](#) URL endpoint for accessing the service.

Value

Tibble of available EMODnet Web Feature Services

Examples

```
emodnet_wfs()
```

layer_attributes_get_names

Names of variables (attributes) available from a dataset (layer) in a data source (service).

Description

Names of variables (attributes) available from a dataset (layer) in a data source (service).

Usage

```
layer_attributes_get_names(  
  wfs = NULL,  
  service = NULL,  
  service_version = NULL,  
  layer  
)
```

Arguments

wfs	A WFSClient R6 object with methods for interfacing an OGC Web Feature Service. From emodnet_init_wfs_client() .
service	the EMODnet OGC WFS service name. For available services, see emodnet_wfs() .
service_version	[Deprecated] the WFS service version. Now always "2.0.0".
layer	character string of layer name. To get info on layers, including layer_name use emodnet_get_wfs_info() .

Value

character vector of layer attribute (variable) names.

See Also

Attributes metadata: [layer_attribute_descriptions\(\)](#), [layer_attribute_inspect\(\)](#), [layer_attributes_summarise\(\)](#), [layer_attributes_tbl\(\)](#)

Examples

```
layer_attributes_get_names(  
  service = "biology",  
  layer = "mediseh_zostera_m_pnt"  
)
```

layer_attributes_summarise
Get summaries of layer attributes (variables)

Description

Get summaries of layer attributes (variables)

Usage

```
layer_attributes_summarise(  
  wfs = NULL,  
  service = NULL,  
  service_version = NULL,  
  layer  
)
```

Arguments

wfs	A WFSClient R6 object with methods for interfacing an OGC Web Feature Service. From emodnet_init_wfs_client() .
service	the EMODnet OGC WFS service name. For available services, see emodnet_wfs() .
service_version	[Deprecated] the WFS service version. Now always "2.0.0".
layer	character sting of layer name. To get info on layers, including layer_name use emodnet_get_wfs_info() .

Value

output of summary() on the attributes (variables) in a given layer for a given service.

See Also

Attributes metadata: [layer_attribute_descriptions\(\)](#), [layer_attribute_inspect\(\)](#), [layer_attributes_get_names\(\)](#), [layer_attributes_tbl\(\)](#)

Examples

```
layer_attributes_summarise(  
  service = "biology",  
  layer = "mediseh_zostera_m_pnt"  
)
```

layer_attributes_tbl *Possible values of variables (attributes) in a dataset (layer) from a data source (service).*

Description

Get layer attribute values tibble

Usage

```
layer_attributes_tbl(wfs = NULL, service = NULL, service_version = NULL, layer)
```

Arguments

wfs	A WFSClient R6 object with methods for interfacing an OGC Web Feature Service. From emodnet_init_wfs_client() .
service	the EMODnet OGC WFS service name. For available services, see emodnet_wfs() .
service_version	[Deprecated] the WFS service version. Now always "2.0.0".
layer	character sting of layer name. To get info on layers, including layer_name use emodnet_get_wfs_info() .

Details

Request excluding spatial information can be significantly faster. Can be useful for inspecting attribute values and constructing feature filters for more targeted and faster layer download.

Value

tibble of layer attribute (variable) values with geometry column removed.

See Also

Attributes metadata: [layer_attribute_descriptions\(\)](#), [layer_attribute_inspect\(\)](#), [layer_attributes_get_names\(\)](#), [layer_attributes_summarise\(\)](#)

Examples

```
layer_attributes_tbl(service = "biology", layer = "mediseh_zostera_m_pnt")
```

layer_attribute_descriptions

Variables available in a dataset (layer) from a data source (service).

Description

Get layer attribute description

Usage

```
layer_attribute_descriptions(
  wfs = NULL,
  service = NULL,
  service_version = NULL,
  layer
)
```

Arguments

wfs	A WFSClient R6 object with methods for interfacing an OGC Web Feature Service. From emodnet_init_wfs_client() .
service	the EMODnet OGC WFS service name. For available services, see emodnet_wfs() .
service_version	[Deprecated] the WFS service version. Now always "2.0.0".
layer	character sting of layer name. To get info on layers, including layer_name use emodnet_get_wfs_info() .

Value

data.frame containing layer attribute descriptions (metadata).

See Also

Attributes metadata: [layer_attribute_inspect\(\)](#), [layer_attributes_get_names\(\)](#), [layer_attributes_summarise\(\)](#), [layer_attributes_tbl\(\)](#)

Examples

```
layer_attribute_descriptions(
  service = "biology",
  layer = "mediseh_zostera_m_pnt"
)
```

layer_attribute_inspect

Summary of individual variable (attribute) in a dataset (layer) from a data source (service).

Description

Inspect layer attributes

Usage

```
layer_attribute_inspect(  
  wfs = NULL,  
  service = NULL,  
  service_version = NULL,  
  layer,  
  attribute  
)
```

Arguments

wfs	A WFSClient R6 object with methods for interfacing an OGC Web Feature Service. From emodnet_init_wfs_client() .
service	the EMODnet OGC WFS service name. For available services, see emodnet_wfs() .
service_version	[Deprecated] the WFS service version. Now always "2.0.0".
layer	character string of layer name. To get info on layers, including layer_name use emodnet_get_wfs_info() .
attribute	character string, name of layer attribute (variable). Use layer_attributes_get_names() to get layer attribute names.

Value

Detailed summary of individual attribute (variable). Particularly useful for inspecting factor or character variable levels or unique values.

See Also

Attributes metadata: [layer_attribute_descriptions\(\)](#), [layer_attributes_get_names\(\)](#), [layer_attributes_summary\(\)](#), [layer_attributes_tbl\(\)](#)

Examples

```
wfs <- emodnet_init_wfs_client(service = "biology")  
layer_attributes_get_names(wfs, layer = "mediseh_zostera_m_pnt")  
layer_attribute_inspect(  
  wfs, layer = "mediseh_zostera_m_pnt",
```

12

layer_attribute_inspect

```
attribute = "country"  
)
```

Index

* attributes

layer_attribute_descriptions, 10
layer_attribute_inspect, 11
layer_attributes_get_names, 7
layer_attributes_summarise, 8
layer_attributes_tbl, 9

emodnet_get_all_wfs_info
 (emodnet_get_layer_info), 4
emodnet_get_layer_info, 4
emodnet_get_layers, 2
emodnet_get_wfs_info
 (emodnet_get_layer_info), 4
emodnet_get_wfs_info(), 3, 4, 7–11
emodnet_init_wfs_client, 5, 6
emodnet_init_wfs_client(), 2, 4, 7–11
emodnet_wfs, 6
emodnet_wfs(), 2, 4, 5, 7–11

layer_attribute_descriptions, 7–9, 10,
 11
layer_attribute_inspect, 7–10, 11
layer_attributes_get_names, 7, 8–11
layer_attributes_get_names(), 11
layer_attributes_summarise, 7, 8, 9–11
layer_attributes_tbl, 7, 8, 9, 10, 11

ows4R::WFSClient, 6