

Package: fluidsynth (via r-universe)

June 28, 2024

Type Package

Title Read and Play Digital Music (MIDI)

Version 1.0.0

Description Bindings to 'libfluidsynth' to parse and synthesize MIDI files. It can read MIDI into a data frame, play it on the local audio device, or convert into an audio file.

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.1

Imports av, rappdirs

SystemRequirements fluidsynth: fluidsynth-devel (rpm) or libfluidsynth-dev (deb). On Linux you also need a soundfont provided by 'fluid-soundfont-gm' (Fedora) or 'sf3-soundfont-gm' (Debian/Ubuntu)

URL <https://docs.ropensci.org/fluidsynth/>
<https://ropensci.r-universe.dev/fluidsynth>

BugReports <https://github.com/ropensci/fluidsynth/issues>

Repository <https://ropensci.r-universe.dev>

RemoteUrl <https://github.com/ropensci/fluidsynth>

RemoteRef main

RemoteSha 2c7e4fcb9f8b1e7ec0944ced982ff33d1faecb88

Contents

fluidsynth_settings	2
midi_play	3
soundfonts	4

Index

5

fluidsynth_settings *Fluidsynth settings*

Description

Get available settings and their types. See [fluidsynth docs](#) for more information on the available options.

Usage

```
fluidsynth_setting_list()  
fluidsynth_setting_options(setting)  
fluidsynth_setting_default(setting)  
libfluidsynth_version()
```

Arguments

setting string with one of the options listed in [fluidsynth_setting_list\(\)](#), see examples.

Value

a list with available options

References

[FluidSynth Settings Reference](#)

See Also

Other fluidsynth: [midi_play\(\)](#), [soundfonts](#)

Examples

```
# List available settings:  
fluidsynth_setting_list()  
fluidsynth_setting_options('audio.driver')  
fluidsynth_setting_default('synth.sample-rate')
```

midi_play	<i>Play or convert a midi file</i>
-----------	------------------------------------

Description

Play a midi file to your audio device, render it to a file, or parse the raw data. Additional settings can be specified, see [fluidsynth_setting_list](#) for available options.

Usage

```
midi_play(  
    midi = demo_midi(),  
    soundfont = soundfont_path(),  
    audio.driver = NULL,  
    settings = list(),  
    verbose = interactive()  
)  
  
midi_convert(  
    midi = demo_midi(),  
    soundfont = soundfont_path(),  
    output = "output.mp3",  
    settings = list(),  
    verbose = interactive()  
)  
  
midi_read(midi = demo_midi(), verbose = FALSE)  
  
demo_midi()
```

Arguments

midi	path to the midi file
soundfont	path to the soundfont
audio.driver	which audio driver to use, see fluidsynth docs
settings	a named vector with additional settings from fluidsynth_setting_list()
verbose	print some progress status to the terminal
output	filename of the output. The out

Details

The `midi_convert` function internally uses `fluidsynth` to generate a raw wav file, and then `av::av_audio_convert()` to convert into the requested about format. See `av::av_muxers()` for supported output formats and their corresponding file extension.

You need a soundfont to synthesize midi, see the [soundfonts](#) page. On Linux you may also need to specify an `audio.driver` that works for your hardware, although on recent distributions the defaults generally work.

Value

`midi_read` returns data frame with midi events.

See Also

Other fluidsynth: [fluidsynth_settings](#), [soundfonts](#)

Examples

```
df <- midi_read(demo_midi())
```

soundfonts

Managing soundfonts

Description

FluidSynth requires a soundfont to synthesize a midi. On Linux distributions some soundfonts are often preinstalled, though their quality varies. If your midi sounds very poor, try using another soundfont.

Usage

```
soundfont_path(download = FALSE)  
soundfont_download()
```

Arguments

`download` automatically download soundfont if none exists.

Details

[GeneralUser-GS](#) by S. Christian Collins is a nice free soundfont. You can use `soundfont_download()` to install a copy of this soundbank for use by this package.

Value

the path to a local soundfont to synthesize a midi file.

See Also

Other fluidsynth: [fluidsynth_settings](#), [midi_play](#)()

Index

- * **fluidsynth**
 - fluidsynth_settings, [2](#)
 - midi_play, [3](#)
 - soundfonts, [4](#)
- av::av_audio_convert(), [3](#)
- av::av_muxers(), [3](#)
- demo_midi (midi_play), [3](#)
- fluidsynth_setting_default
 - (fluidsynth_settings), [2](#)
- fluidsynth_setting_list, [3](#)
- fluidsynth_setting_list
 - (fluidsynth_settings), [2](#)
- fluidsynth_setting_list(), [2](#), [3](#)
- fluidsynth_setting_options
 - (fluidsynth_settings), [2](#)
- fluidsynth_settings, [2](#), [4](#)
- libfluidsynth_version
 - (fluidsynth_settings), [2](#)
- midi_convert (midi_play), [3](#)
- midi_play, [2](#), [3](#), [4](#)
- midi_read (midi_play), [3](#)
- soundfont_download (soundfonts), [4](#)
- soundfont_path (soundfonts), [4](#)
- soundfonts, [2](#)–[4](#), [4](#)