

Package: jq (via r-universe)

October 30, 2026

Title Client for 'jq', a 'JSON' Processor

Description Client for 'jq', a 'JSON' processor
(<https://jqlang.github.io/jq/>), written in C. 'jq' allows the following with 'JSON' data: index into, parse, do calculations, cut up and filter, change key names and values, perform conditionals and comparisons, and more.

Version 1.4.0

Depends R (>= 3.1.2)

License MIT + file LICENSE

Encoding UTF-8

Language en-US

LazyData true

URL <https://docs.ropensci.org/jqr/> <https://ropensci.r-universe.dev/jqr>

BugReports <https://github.com/ropensci/jqr/issues>

SystemRequirements libjq: jq-devel (rpm) or libjq-dev (deb)

Imports magrittr, lazyeval

Suggests jsonlite, testthat

RoxygenNote 7.3.2.9000

Config/pak/sysreqs libjq-dev

Repository <https://ropensci.r-universe.dev>

Date/Publication 2024-12-14 23:26:27 UTC

RemoteUrl <https://github.com/ropensci/jqr>

RemoteRef HEAD

RemoteSha f920d08d7c59e97e4ef9b1b90fb4c19a57479348

Contents

at	2
build	3
combine	4
commits	5
dot	5
funcs	6
index	6
jq	8
jq_flags	9
jqr	10
jqr_new	12
keys	12
logicaltests	13
manip	14
maths	17
paths	20
peek	20
rangej	21
recurse	21
select	22
sortj	23
string	24
types	24
vars	25
Index	27

at	<i>Format strings and escaping</i>
----	------------------------------------

Description

Format strings and escaping

Usage

at(.data, ...)

at_(.data, ..., .dots)

Arguments

- | | |
|-------|---|
| .data | input. This can be JSON input, or an object of class jqr that has JSON and query params combined, which is passed from function to function when using the jqr DSL. |
| ... | Comma separated list of unquoted variable names |

.dots	Used to work around non-standard evaluation
dots	dots

Examples

```
x <- '{"user":"jqlang","titles":["JQ Primer", "More JQ"]}'
x %>% at(base64) %>% peek
x %>% at(base64)
x %>% index() %>% at(base64)

y <- '["fo", "foo", "barfoo", "foobar", "barfoob"]'
y %>% index() %>% at(base64)

## prepare for shell use
y %>% index() %>% at(sh)

## rendered as csv with double quotes
z <- '[1, 2, 3, "a"]'
z %>% at(csv)

## rendered as csv with double quotes
z %>% index()
z %>% index() %>% at(text)

## % encode for URI's
#### DOESNT WORK -----

## html escape
#### DOESNT WORK -----

## serialize to json
#### DOESNT WORK -----
```

build	<i>Build arrays and objects</i>
-------	---------------------------------

Description

Build arrays and objects

Usage

```
build_array(.data, ...)

build_array_(.data, ..., .dots)

build_object(.data, ...)

build_object_(.data, ..., .dots)
```

Arguments

<code>.data</code>	input. This can be JSON input, or an object of class <code>jqr</code> that has JSON and query params combined, which is passed from function to function when using the <code>jqr</code> DSL.
<code>...</code>	Comma separated list of unquoted variable names
<code>.dots</code>	Used to work around non-standard evaluation
<code>dots</code>	<code>dots</code>

Examples

```
## BUILD ARRAYS
x <- '{"user": "jqlang", "projects": ["jq", "wikiflow"]}'
jq(x, "[.user, .projects[]]")
x %>% build_array(.user, .projects[])

jq('[1, 2, 3]', '[.[] | . * 2]')
'[1, 2, 3]' %>% build_array(.[] | . * 2)

## BUILD OBJECTS
 '{"foo": 5, "bar": 7}' %>% build_object(a = .foo) %>% peek
 '{"foo": 5, "bar": 7}' %>% build_object(a = .foo)

# using json dataset, just first element
x <- commits %>% index(0)
x %>%
  build_object(message = .commit.message, name = .commit.committer.name)
x %>% build_object(shas = .commit.tree.shas, author = .author.login)

# using json dataset, all elements
x <- index(commits)
x %>% build_object(message = .commit.message, name = .commit.committer.name)
x %>% build_object(shas = .shas, name = .commit.committer.name)

# many JSON inputs
 '{"foo": 5, "bar": 7} {"foo": 50, "bar": 7} {"foo": 500, "bar": 7}' %>%
  build_object(hello = .foo)
```

 combine

Combine json pieces

Description

Combine json pieces

Usage

```
combine(x)
```

Arguments

x Input, of class json

Examples

```
x <- '{"foo": 5, "bar": 7}' %>% select(a = .foo)
combine(x)

(x <- commits %>% index() %>%
  select(sha = .sha, name = .commit.committer.name))
combine(x)
```

commits	<i>GitHub Commits Data</i>
---------	----------------------------

Description

GitHub Commits Data

Format

A character string of json github commits data for the jq repo.

dot	<i>dot and related functions</i>
-----	----------------------------------

Description

dot and related functions

Usage

```
dot(.data)

dot_(.data, dots = ".")

dotstr(.data, ...)

dotstr_(.data, ..., .dots)
```

Arguments

.data	input. This can be JSON input, or an object of class jqv that has JSON and query params combined, which is passed from function to function when using the jqv DSL.
dots	dots
...	Comma separated list of unquoted variable names
.dots	Used to work around non-standard evaluation

Examples

```
str <- '[{"name":"JSON", "good":true}, {"name":"XML", "good":false}]'
str %>% dot
str %>% index %>% dotstr(name)
'{"foo": 5, "bar": 8}' %>% dot
'{"foo": 5, "bar": 8}' %>% dotstr(foo)
'{"foo": {"bar": 8}}' %>% dotstr(foo.bar)
```

funs	Define and use functions
------	--------------------------

Description

Define and use functions

Usage

```
funs(.data, fxn, action)
```

Arguments

.data	input
fxn	A function definition, without def (added internally)
action	What to do with the function on the data

Examples

```
jq("[1,2,10,20]", 'def increment: . + 1; map(increment)')
"[1,2,10,20]" %>% funs('increment: . + 1', 'map(increment)')
"[1,2,10,20]" %>% funs('increment: . / 100', 'map(increment)')
"[1,2,10,20]" %>% funs('increment: . / 100', 'map(increment)')
'[[1,2],[10,20]]' %>% funs('addvalue(f): f as $x | map(. + $x)', 'addvalue(.[0])')
"[1,2]" %>% funs('f(a;b;c;d;e;f): [a+1,b,c,d,e,f]', 'f(.[0];.[1];.[0];.[0];.[0])')
"[1,2,3,4]" %>% funs('fac: if . == 1 then 1 else . * (. - 1 | fac) end', '.[.] | fac')
```

index	index and related functions
-------	-----------------------------

Description

index and related functions

Usage

```

index(.data, ...)

index_(.data, ..., .dots)

indexif(.data, ...)

indexif_(.data, ..., .dots)

dotindex(.data, ...)

dotindex_(.data, ..., .dots)

```

Arguments

<code>.data</code>	input. This can be JSON input, or an object of class <code>jqr</code> that has JSON and query params combined, which is passed from function to function when using the <code>jqr</code> DSL.
<code>...</code>	Comma separated list of unquoted variable names
<code>.dots</code>	Used to work around non-standard evaluation
<code>dots</code>	<code>dots</code>

Details

- `index/index_` - queries like: `.[], .[0], .[1:5], .["foo"]`
- `indexif/indexif_` - queries like: `.["foo"]?`
- `dotindex/dotindex_` - queries like: `.[].foo, .[].foo.bar`

Examples

```

str <- '[{"name":"JSON", "good":true}, {"name":"XML", "good":false}]'
str %>% index
'{"name":"JSON", "good":true}' %>% indexif(name)
'{"name":"JSON", "good":true}' %>% indexif(good)
'{"name":"JSON", "good":true}' %>% indexif(that)
'{"a": 1, "b": 1}' %>% index
'[]' %>% index
'[{"name":"JSON", "good":true}, {"name":"XML", "good":false}]' %>% index(0)
'["a","b","c","d","e"]' %>% index(2)
'["a","b","c","d","e"]' %>% index('2:4')
'["a","b","c","d","e"]' %>% index('2:5')
'["a","b","c","d","e"]' %>% index(':3')
'["a","b","c","d","e"]' %>% index('-2:')

str %>% index %>% select(bad = .name)

'[{"name":"JSON", "good":true}, {"name":"XML", "good":false}]' %>%
  dotindex(name)
'[{"name":"JSON", "good":true}, {"name":"XML", "good":false}]' %>%

```

```

dotindex(good)
'["name":"JSON", "good":{"foo":5}}, {"name":"XML", "good":{"foo":6}}]' %>%
  dotindex(good)
'["name":"JSON", "good":{"foo":5}}, {"name":"XML", "good":{"foo":6}}]' %>%
  dotindex(good.foo)

```

jq

Execute a query with jq

Description

jq is meant to work with the high level interface in this package. jq also provides access to the low level interface in which you can use jq query strings just as you would on the command line. Output gets class of json, and pretty prints to the console for easier viewing. jqr doesn't do pretty printing.

Usage

```

jq(x, ...)

## S3 method for class 'jqr'
jq(x, ...)

## S3 method for class 'character'
jq(x, ..., flags = jq_flags())

## S3 method for class 'json'
jq(x, ..., flags = jq_flags())

## S3 method for class 'connection'
jq(x, ..., flags = jq_flags(), out = NULL)

```

Arguments

x	json object or character string with json data. this can be one or more valid json objects
...	character specification of jq query. Each element in ... will be combined with " ", which is convenient for long queries.
flags	See jq_flags
out	a filename, callback function, connection object to stream output. Set to 'NULL' to buffer all output and return a character vector.

See Also

[peek](#)

Examples

```
'{"a": 7}' %>% do(.a + 1)
'[8,3,null,6]' %>% sortj

x <- '["message": "hello", "name": "jenn"},
{"message": "world", "name": "beth"}]'
jq(index(x))

jq('{"a": 7, "b": 4}', 'keys')
jq('[8,3,null,6]', 'sort')

# many json inputs
jq(c("[123, 456]", "[77, 88, 99]", "[41]"), ".[]")
# Stream from connection
tmp <- tempfile()
writeLines(c("[123, 456]", "[77, 88, 99]", "[41]"), tmp)
jq(file(tmp), ".[]")

## Not run:
# from a url
x <- 'http://jeroen.github.io/data/diamonds.json'
jq(url(x), ".[]")

# from a file
file <- file.path(tempdir(), "diamonds_nd.json")
download.file(x, destfile = file)
jq(file(file), ".carat")
jq(file(file), "select(.carat > 1.5)")
jq(file(file), 'select(.carat > 4 and .cut == "Fair")')

## End(Not run)
```

jq_flags

Flags for use with jq

Description

The flags function is provided for the high-level DSL approach, whereas the jq_flags function is used to provide the low-level jq with the appropriate flags.

Usage

```
jq_flags(
  pretty = FALSE,
  ascii = FALSE,
  color = FALSE,
  sorted = FALSE,
  stream = FALSE,
  seq = FALSE
```

```
)

flags(
  .data,
  pretty = FALSE,
  ascii = FALSE,
  color = FALSE,
  sorted = FALSE,
  stream = FALSE,
  seq = FALSE
)
```

Arguments

<code>pretty</code>	Pretty print the json (different to jsonlite’s pretty printing).
<code>ascii</code>	Force jq to produce pure ASCII output with non-ASCII characters replaced by equivalent escape sequences.
<code>color</code>	Add ANSI escape sequences for coloured output
<code>sorted</code>	Output fields of each object with keys in sorted order
<code>stream</code>	Parse the input in streaming fashion, outputting arrays of path and leaf values like <code>jq --stream</code> command line.
<code>seq</code>	Use the application/json-seq MIME type scheme for separating JSON like the <code>jq --seq</code> command line.
<code>.data</code>	A <i>jq</i> object.

Examples

```
'{"a": 7, "z":0, "b": 4}' %>% flags(sorted = TRUE)
'{"a": 7, "z":0, "b": 4}' %>% dot %>% flags(sorted = TRUE)
jq('{"a": 7, "z":0, "b": 4}', ".") %>% flags(sorted = TRUE)
jq('{"a": 7, "z":0, "b": 4}', ".", flags = jq_flags(sorted = TRUE))
```

<i>jq</i>	<i>jq</i>
-----------	-----------

Description

An R client for the C library *jq*

Low-level

Low level interface, in which you can execute ‘*jq*’ code just as you would on the command line. Available via [jq](#)

High-level DSL

High-level, uses a suite of functions to construct queries. Queries are constructed, then executed internally with `jq`

Pipes

The high level DSL supports piping, though you don't have to use pipes.

NSE and SE

Most DSL functions have NSE (non-standard evaluation) and SE (standard evaluation) versions, which make `jq` easy to use for interactive use as well as programming.

jq version

We link to `jq` through the installed version on your system, so the version can vary. Run `jq --version` to get your `jq` version

indexing

note that `jq` indexing starts at 0, whereas R indexing starts at 1. So when you want the first thing in an array using `jq`, for example, you want 0, not 1

output data format

Note that with both the low level interface and the high level DSL, we print the output to look like a valid JSON object to make it easier to look at. However, it's important to know that the output is really just a simple character string or vector of strings - it's just the print function that pretty prints it and makes it look like a single JSON object. What `jq` is giving you often is a stream of valid JSON objects, each one of which is valid, but altogether are not valid. However, a trick you can do is to wrap your `jq` program in brackets like `[.[]]` instead of `.[]` to give a single JSON object

Related to above, you can use the function provided `string` with the high level DSL to get back a character string instead of pretty printed version

Author(s)

Maintainer: Jeroen Ooms <jeroen@gmail.com>

Authors:

- Rich FitzJohn <rich.fitzjohn@gmail.com>
- Scott Chamberlain <myrmecocystus@gmail.com>
- Stefan Milton Bache <stefan@stefanbache.dk>

See Also

Useful links:

- <https://docs.ropensci.org/jqr/>
- <https://ropensci.r-universe.dev/jqr>

- Report bugs at <https://github.com/ropensci/jqr/issues>

jqr_new

JQ Streaming API

Description

Low level JQ API. First create a program using a ‘query’ and ‘flags’ and then feed pieces of data.

Usage

```
jqr_new(query, flags = jq_flags())
```

```
jqr_feed(jqr_program, json, unlist = TRUE, finalize = FALSE)
```

Arguments

query	string with a valid jq program
flags	See jq_flags
jqr_program	object returned by [jqr_new]
json	character vector with json data. If the JSON object is incomplete, you must set ‘finalize’ to ‘FALSE’ otherwise you get an error.
unlist	if ‘TRUE’ returns a single character vector with all output for each each string in ‘json’ input
finalize	completes the parsing and verifies that the JSON string is valid. Set this to ‘TRUE’ when feeding the final piece of data.

Examples

```
program <- jqr_new("[]")
jqr_feed(program, c("[123, 456]", "[77, 88, 99]"))
jqr_feed(program, c("[41, 234]"))
jqr_feed(program, "", finalize = TRUE)
```

keys

Operations on keys, or by keys

Description

keys takes no input, and retrieves keys. del deletes provided keys. haskey checks if a json string has a key, or the input array has an element at the given index.

Usage

```

keys(.data)

del(.data, ...)

del_(.data, ..., .dots)

haskey(.data, ...)

haskey_(.data, ..., .dots)

```

Arguments

<code>.data</code>	input. This can be JSON input, or an object of class <code>jqr</code> that has JSON and query params combined, which is passed from function to function when using the <code>jqr</code> DSL.
<code>...</code>	Comma separated list of unquoted variable names
<code>.dots</code>	Used to work around non-standard evaluation
<code>dots</code>	<code>dots</code>

Examples

```

# get keys
str <- '{"foo": 5, "bar": 7}'
jq(str, "keys")
str %>% keys()

# delete by key name
jq(str, "del(.bar)")
str %>% del(bar)

# check for key existence
str3 <- '[[0,1], ["a","b","c"]]'
jq(str3, "map(has(2))")
str3 %>% haskey(2)
jq(str3, "map(has(1,2))")
str3 %>% haskey(1,2)

## many JSON inputs
'{"foo": 5, "bar": 7} {"hello": 5, "world": 7}' %>% keys
'{"foo": 5, "bar": 7} {"hello": 5, "bar": 7}' %>% del(bar)

```

logicaltests

Logical tests

Description

Logical tests

Usage

```
allj(.data)
```

```
anyj(.data)
```

Arguments

`.data` input. This can be JSON input, or an object of class `jqr` that has JSON and query params combined, which is passed from function to function when using the `jqr` DSL.

Examples

```
# any
'[true, false]' %>% anyj
'[false, false]' %>% anyj
'[]' %>% anyj

# all
'[true, false]' %>% allj
'[true, true]' %>% allj
'[]' %>% allj

## many JSON inputs
'[true, false] [true, true] [false, false]' %>% anyj
'[true, false] [true, true] [false, false]' %>% allj
```

manip

Manipulation operations

Description

Manipulation operations

Usage

```
join(.data, ...)
```

```
join_(.data, ..., .dots)
```

```
splitj(.data, ...)
```

```
splitj_(.data, ..., .dots)
```

```
ltrimstr(.data, ...)
```

```
ltrimstr_(.data, ..., .dots)
```

```
rtrimstr(.data, ...)  
rtrimstr_(.data, ..., .dots)  
startswith(.data, ...)  
startswith_(.data, ..., .dots)  
endswith(.data, ...)  
endswith_(.data, ..., .dots)  
index_loc(.data, ...)  
index_loc_(.data, ..., .dots)  
rindex_loc(.data, ...)  
rindex_loc_(.data, ..., .dots)  
indices(.data, ...)  
indices_(.data, ..., .dots)  
tojson(.data)  
fromjson(.data)  
tostring(.data)  
tonumber(.data)  
contains(.data, ...)  
contains_(.data, ..., .dots)  
uniquej(.data, ...)  
uniquej_(.data, ..., .dots)  
group(.data, ...)  
group_(.data, ..., .dots)
```

Arguments

<code>.data</code>	input. This can be JSON input, or an object of class <code>jqr</code> that has JSON and query params combined, which is passed from function to function when using the <code>jqr</code> DSL.
--------------------	---

...	Comma separated list of unquoted variable names
.dots	Used to work around non-standard evaluation
dots	dots

Examples

```
# join
str <- '["a","b,c,d","e"]'
jq(str, 'join(", ")')
str %>% join
str %>% join(`;`)
str %>% join(`yep`)
## many JSON inputs
'["a","b,c,d","e"] ["a","f,e,f"]' %>% join(`---`)

# split
jq('"a, b,c,d, e"', 'split(", ")')

# ltrimstr
jq('["fo", "foo", "barfoo", "foobar", "afoo"]', '[.[]|ltrimstr("foo")]')
'["fo", "foo", "barfoo", "foobar", "afoo"]' %>% index() %>% ltrimstr(foo)

# rtrimstr
jq('["fo", "foo", "barfoo", "foobar", "foob"]', '[.[]|rtrimstr("foo")]')
'["fo", "foo", "barfoo", "foobar", "foob"]' %>% index() %>% rtrimstr(foo)

# startswith
str <- '["fo", "foo", "barfoo", "foobar", "barfoob"]'
jq(str, '[.[]|startswith("foo")]')
str %>% index %>% startswith(foo)
## many JSON inputs
'["fo", "foo"] ["barfoo", "foobar", "barfoob"]' %>% index %>% startswith(foo)

# endswith
jq(str, '[.[]|endswith("foo")]')
str %>% index %>% endswith(foo)
str %>% index %>% endswith_("foo")
str %>% index %>% endswith(bar)
str %>% index %>% endswith_("bar")
## many JSON inputs
'["fo", "foo"] ["barfoo", "foobar", "barfoob"]' %>% index %>% endswith(foo)

# get index (location) of a character
## input has to be quoted
str <- '"a,b, cd, efg, hijk"'
str %>% index_loc(", ")
str %>% index_loc(",")
str %>% index_loc("j")
str %>% rindex_loc(", ")
str %>% indices(", ")

# tojson, fromjson, tostring, tonumber
```

```

'[1, "foo", ["foo"]]' %>% index %>% toString
'[1, "1"]' %>% index %>% tonumber
'[1, "foo", ["foo"]]' %>% index %>% tojson
'[1, "foo", ["foo"]]' %>% index %>% tojson %>% fromjson

# contains
'"foobar"' %>% contains("bar")
'["foobar", "foobaz", "blarp"]' %>% contains(`["baz", "bar"]`)
'["foobar", "foobaz", "blarp"]' %>% contains(`["bazzzzz", "bar"]`)
str <- '{"foo": 12, "bar": [1,2,{"barp":12, "blip":13}]}'
str %>% contains(`{foo: 12, bar: [{barp: 12}]}`)
str %>% contains(`{foo: 12, bar: [{barp: 15}]}`)

# unique
'[1,2,5,3,5,3,1,3]' %>% uniquej
str <- '{"foo": 1, "bar": 2}, {"foo": 1, "bar": 3}, {"foo": 4, "bar": 5}]'
str %>% uniquej(foo)
str %>% uniquej("foo")
'["chunky", "bacon", "kitten", "cicada", "asparagus"]' %>% uniquej(length)

# group
x <- '{"foo":1, "bar":10}, {"foo":3, "bar":100}, {"foo":1, "bar":1}]'
x %>% group(foo)
x %>% group_("foo")

```

maths

*Math operations***Description**

Math operations

Usage

do(.data, ...)

do_(.data, ..., .dots)

lengthj(.data)

sqrtj(.data)

floorj(.data)

minj(.data, ...)

minj_(.data, ..., .dots)

maxj(.data, ...)

```

maxj_(.data, ..., .dots)

ad(.data)

map(.data, ...)

map_(.data, ..., .dots)

```

Arguments

<code>.data</code>	input. This can be JSON input, or an object of class <code>jqr</code> that has JSON and query params combined, which is passed from function to function when using the <code>jqr</code> DSL.
<code>...</code>	Comma separated list of unquoted variable names
<code>.dots</code>	Used to work around non-standard evaluation
<code>dots</code>	<code>dots</code>

Examples

```

# do math
jq('{"a": 7}', '.a + 1')
# adding null gives back same result
jq('{"a": 7}', '.a + null')
jq('{"a": 7}', '.a += 1')
'{"a": 7}' %>% do(.a + 1)
# '{"a": 7}' %>% do(.a += 1) # this doesn't work quite yet
'{"a": [1,2], "b": [3,4]}' %>% do(.a + .b)
'{"a": [1,2], "b": [3,4]}' %>% do(.a - .b)
'{"a": 3}' %>% do(4 - .a)
'["xml", "yaml", "json"]' %>% do(' - ["xml", "yaml"]')
'5' %>% do(10 / . * 3)
## many JSON inputs
'{"a": [1,2], "b": [3,4]} {"a": [1,5], "b": [3,10]}' %>% do(.a + .b)

# comparisons
'[5,4,2,7]' %>% index() %>% do(. < 4)
'[5,4,2,7]' %>% index() %>% do(. > 4)
'[5,4,2,7]' %>% index() %>% do(. <= 4)
'[5,4,2,7]' %>% index() %>% do(. >= 4)
'[5,4,2,7]' %>% index() %>% do(. == 4)
'[5,4,2,7]' %>% index() %>% do(. != 4)
## many JSON inputs
'[5,4,2,7] [4,3,200,0.1]' %>% index() %>% do(. < 4)

# length
'[[1,2], "string", {"a":2}, null]' %>% index %>% lengthj

# sqrt
'9' %>% sqrtj
## many JSON inputs

```

```

'9 4 5' %>% sqrtj

# floor
'3.14159' %>% floorj
## many JSON inputs
'3.14159 30.14 45.9' %>% floorj

# find minimum
'[5,4,2,7]' %>% minj
'["foo":1, "bar":14], {"foo":2, "bar":3}]' %>% minj
'["foo":1, "bar":14], {"foo":2, "bar":3}]' %>% minj(foo)
'["foo":1, "bar":14], {"foo":2, "bar":3}]' %>% minj(bar)
## many JSON inputs
'["foo":1], {"foo":14}] [{"foo":2}, {"foo":3}]' %>% minj(foo)

# find maximum
'[5,4,2,7]' %>% maxj
'["foo":1, "bar":14], {"foo":2, "bar":3}]' %>% maxj
'["foo":1, "bar":14], {"foo":2, "bar":3}]' %>% maxj(foo)
'["foo":1, "bar":14], {"foo":2, "bar":3}]' %>% maxj(bar)
## many JSON inputs
'["foo":1], {"foo":14}] [{"foo":2}, {"foo":3}]' %>% maxj(foo)

# increment values
## requires special % operators, they get escaped internally
'{"foo": 1}' %>% do(.foo %+=% 1)
'{"foo": 1}' %>% do(.foo %-= % 1)
'{"foo": 1}' %>% do(.foo %*=% 4)
'{"foo": 1}' %>% do(.foo %/= % 10)
'{"foo": 1}' %>% do(.foo %//=% 10)
### fix me - %= doesn't work
# '{"foo": 1}' %>% do(.foo %%= % 10)
## many JSON inputs
'{"foo": 1} {"foo": 2} {"foo": 3}' %>% do(.foo %+=% 1)

# add
'["a","b","c"]' %>% ad
'[1, 2, 3]' %>% ad
'[]' %>% ad
## many JSON inputs
'["a","b","c"] ["d","e","f"]' %>% ad

# map
## as far as I know, this only works with numbers, thus it's
## in the maths section
'[1, 2, 3]' %>% map(.+1)
'[1, 2, 3]' %>% map(. / 1)
'[1, 2, 3]' %>% map(. * 4)
# many JSON inputs
'[1, 2, 3] [100, 200, 300] [1000, 2000, 30000]' %>% map(.+1)

```

paths	<i>Outputs paths to all the elements in its input</i>
-------	---

Description

Outputs paths to all the elements in its input

Usage

```
paths(.data)
```

Arguments

.data	input
-------	-------

Examples

```
'[1,[[[{"a":2}]]]' %>% paths
'[{ "name": "JSON", "good": true}, {"name": "XML", "good": false}]' %>% paths
```

peek	<i>Peek at a query</i>
------	------------------------

Description

Prints the query resulting from jq all in one character string just as you would execute it on the command line. Output gets class of json, and pretty prints to the console for easier viewing.

Usage

```
peek(.data)
```

Arguments

.data	(list) input, using higher level interface
-------	--

See Also

[jq.](#)

Examples

```
'{"a": 7}' %>% do(.a + 1) %>% peek
'[8,3,null,6]' %>% sortj %>% peek
```

rangej	<i>Produce range of numbers</i>
--------	---------------------------------

Description

Produce range of numbers

Usage

```
rangej(x, array = FALSE)
```

Arguments

x	Input, single number or number range.
array	(logical) Create array. Default: FALSE

Examples

```
2:4 %>% rangej
2:1000 %>% rangej
1 %>% rangej
4 %>% rangej
```

recurse	<i>Search through a recursive structure - extract data from all levels</i>
---------	--

Description

Search through a recursive structure - extract data from all levels

Usage

```
recurse(.data, ...)  
recurse_(.data, ..., .dots)
```

Arguments

.data	input. This can be JSON input, or an object of class jqr that has JSON and query params combined, which is passed from function to function when using the jqr DSL.
...	Comma separated list of unquoted variable names
.dots	Used to work around non-standard evaluation
dots	dots

Examples

```
x <- '{"name": "/", "children": [
  {"name": "/bin", "children": [
    {"name": "/bin/lis", "children": []},
    {"name": "/bin/sh", "children": []}]},
  {"name": "/home", "children": [
    {"name": "/home/stephen", "children": [
      {"name": "/home/stephen/jq", "children": []}]}}]}'
x %>% recurse(.children[]) %>% build_object(name)
x %>% recurse(.children[]) %>% build_object(name) %>% string
```

select

Select - filtering

Description

The function `select(foo)` produces its input unchanged if `foo` returns `TRUE` for that input, and produces no output otherwise

Usage

```
select(.data, ...)
```

```
select_(.data, ..., .dots)
```

Arguments

<code>.data</code>	input. This can be JSON input, or an object of class <code>jqr</code> that has JSON and query params combined, which is passed from function to function when using the <code>jqr</code> DSL.
<code>...</code>	Comma separated list of unquoted variable names
<code>.dots</code>	Used to work around non-standard evaluation
<code>dots</code>	<code>dots</code>

Note

this function has changed what it does dramatically. we were using this function for object construction, which is now done with [build_object](#)

Examples

```
jq('[1,5,3,0,7]', 'map(select(. >= 2))')
'[1,5,3,0,7]' %>% map(select(. >= 2))

 '{"foo": 4, "bar": 7}' %>% select(.foo == 4)
 '{"foo": 5, "bar": 7} {"foo": 4, "bar": 7}' %>% select(.foo == 4)
```

```
'[{"foo": 5, "bar": 7}, {"foo": 4, "bar": 7}]' %>% index() %>%
  select(.foo == 4)
'{"foo": 4, "bar": 7} {"foo": 5, "bar": 7} {"foo": 8, "bar": 7}' %>%
  select(.foo < 6)

x <- '{"foo": 4, "bar": 2} {"foo": 5, "bar": 4} {"foo": 8, "bar": 12}'
jq(x, 'select((.foo < 6) and (.bar > 3))')
jq(x, 'select((.foo < 6) or (.bar > 3))')
x %>% select((.foo < 6) && (.bar > 3))
x %>% select((.foo < 6) || (.bar > 3))

x <- '["foo": 5, "bar": 7], {"foo": 4, "bar": 7}, {"foo": 4, "bar": 9}]'
jq(x, '.[] | select(.foo == 4) | {user: .bar}')
```

sortj

*Sort and related***Description**

Sort and related

Usage

```
sortj(.data, ...)

sortj_(.data, ..., .dots)

reverse(.data)
```

Arguments

.data	input. This can be JSON input, or an object of class <code>jqr</code> that has JSON and query params combined, which is passed from function to function when using the <code>jqr</code> DSL.
...	Comma separated list of unquoted variable names
.dots	Used to work around non-standard evaluation
dots	dots

Examples

```
# sort
'[8,3,null,6]' %>% sortj
'["foo":4, "bar":10], {"foo":3, "bar":100}, {"foo":2, "bar":1}]' %>%
  sortj(foo)

# reverse order
'[1,2,3,4]' %>% reverse
```

```
# many JSON inputs
'[{ "foo":7}, {"foo":4}] [{"foo":300}, {"foo":1}] [{"foo":2}, {"foo":1}]' %>%
  sortj(foo)

'[1,2,3,4] [10,20,30,40] [100,200,300,4000]' %>%
  reverse
```

string	<i>Give back a character string</i>
--------	-------------------------------------

Description

Give back a character string

Usage

```
string(.data)
```

Arguments

.data (list) input, using higher level interface

See Also

[peek](#)

Examples

```
'{"a": 7}' %>% do(.a + 1) %>% string
'[8,3,null,6]' %>% sortj %>% string
```

types	<i>Types and related functions</i>
-------	------------------------------------

Description

Types and related functions

Usage

```
types(.data)

type(.data, ...)

type_(.data, ..., .dots)
```

Arguments

.data	input. This can be JSON input, or an object of class jqr that has JSON and query params combined, which is passed from function to function when using the jqr DSL.
...	Comma separated list of unquoted variable names
.dots	Used to work around non-standard evaluation
dots	dots

Examples

```
# get type information for each element
jq('[0, false, [], {}, null, "hello"]', 'map(type)')
'[0, false, [], {}, null, "hello"]' %>% types
'[0, false, [], {}, null, "hello", true, [1,2,3]]' %>% types

# select elements by type
jq('[0, false, [], {}, null, "hello"]', '.[[] | numbers,booleans')
'[0, false, [], {}, null, "hello"]' %>% index() %>% type(booleans)
```

vars	<i>Variables</i>
------	------------------

Description

Variables

Usage

```
vars(.data, ...)

vars_(.data, ..., .dots)
```

Arguments

.data	input. This can be JSON input, or an object of class jqr that has JSON and query params combined, which is passed from function to function when using the jqr DSL.
...	Comma separated list of unquoted variable names
.dots	Used to work around non-standard evaluation
dots	dots

Examples

```

x <- '{
  "posts": [
    {"title": "Frist psot", "author": "anon"},
    {"title": "A well-written article", "author": "person1"}
  ],
  "realnames": {
    "anon": "Anonymous Coward",
    "person1": "Person McPherson"
  }
}'

x %>% dotstr(posts[])
x %>% dotstr(posts[]) %>% string
x %>% vars(realnames = names) %>% dotstr(posts[]) %>%
  build_object(title, author = "$names[.author]")

```

Index

* datasets

commits, 5

ad (maths), 17

allj (logicaltests), 13

anyj (logicaltests), 13

at, 2

at_ (at), 2

build, 3

build_array (build), 3

build_array_ (build), 3

build_object, 22

build_object (build), 3

build_object_ (build), 3

combine, 4

commits, 5

contains (manip), 14

contains_ (manip), 14

del (keys), 12

del_ (keys), 12

do (maths), 17

do_ (maths), 17

dot, 5

dot_ (dot), 5

dotindex (index), 6

dotindex_ (index), 6

dotstr (dot), 5

dotstr_ (dot), 5

endswith (manip), 14

endswith_ (manip), 14

flags (jq_flags), 9

floorj (maths), 17

fromjson (manip), 14

funcs, 6

group (manip), 14

group_ (manip), 14

haskey (keys), 12

haskey_ (keys), 12

index, 6

index_ (index), 6

index_loc (manip), 14

index_loc_ (manip), 14

indexif (index), 6

indexif_ (index), 6

indices (manip), 14

indices_ (manip), 14

join (manip), 14

join_ (manip), 14

jq, 8, 10, 11, 20

jq_flags, 8, 9, 12

jqr, 10

jqr-package (jqr), 10

jqr_feed (jqr_new), 12

jqr_new, 12

keys, 12

lengthj (maths), 17

logicaltests, 13

ltrimstr (manip), 14

ltrimstr_ (manip), 14

manip, 14

map (maths), 17

map_ (maths), 17

maths, 17

maxj (maths), 17

maxj_ (maths), 17

minj (maths), 17

minj_ (maths), 17

paths, 20

peek, 8, 20, 24

rangej, [21](#)
recurse, [21](#)
recurse_ (recurse), [21](#)
reverse (sortj), [23](#)
rindex_loc (manip), [14](#)
rindex_loc_ (manip), [14](#)
rtrimstr (manip), [14](#)
rtrimstr_ (manip), [14](#)

select, [22](#)
select_ (select), [22](#)
sortj, [23](#)
sortj_ (sortj), [23](#)
splitj (manip), [14](#)
splitj_ (manip), [14](#)
sqrtj (maths), [17](#)
startswith (manip), [14](#)
startswith_ (manip), [14](#)
string, [11](#), [24](#)

tojson (manip), [14](#)
tonumber (manip), [14](#)
tostring (manip), [14](#)
type (types), [24](#)
type_ (types), [24](#)
types, [24](#)

uniquej (manip), [14](#)
uniquej_ (manip), [14](#)

vars, [25](#)
vars_ (vars), [25](#)