

Package: rix (via r-universe)

October 29, 2026

Title Reproducible Data Science Environments with 'Nix'

Version 0.18.6

Description Simplifies the creation of reproducible data science environments using the 'Nix' package manager, as described in Dolstra (2006) <ISBN 90-393-4130-3>. The included ``rix()`` function generates a complete description of the environment as a ``default.nix`` file, which can then be built using 'Nix'. This results in project specific software environments with pinned versions of R, packages, linked system dependencies, and other tools or programming languages such as Python or Julia. Additional helpers make it easy to run R code in 'Nix' software environments for testing and production.

License GPL (>= 3)

URL <https://docs.ropensci.org/rix/>

BugReports <https://github.com/ropensci/rix/issues>

Depends R (>= 2.10)

Imports codetools, curl, jsonlite, sys, utils

Suggests knitr, rmarkdown, testthat

VignetteBuilder knitr

Config/testthat/edition 3

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

Config/roxygen2/version 8.1.0

Config/pak/sysreqs libssl-dev

Repository <https://ropensci.r-universe.dev>

Date/Publication 2026-10-29 20:54:15 UTC

RemoteUrl <https://github.com/ropensci/rix>

RemoteRef HEAD

RemoteSha 7c8a3f78d569e3d87ef7e851f235e3d015746fb3

Contents

available_dates	2
available_df	3
available_r	3
ga_cachix	4
make_launcher	5
nix_build	5
renv2nix	6
rix	9
rix_init	14
setup_cachix	16
tar_nix_ga	18
with_nix	18
Index	22

available_dates	<i>List Available Dates for R and Bioconductor Releases</i>
-----------------	---

Description

List Available Dates for R and Bioconductor Releases

Usage

available_dates()

Value

A character vector containing the available dates

See Also

Other available versions: [available_df\(\)](#), [available_r\(\)](#)

Examples

available_dates()

available_df	<i>Return Data Frame with R, Bioc Versions and Supported Platforms</i>
--------------	--

Description

Return Data Frame with R, Bioc Versions and Supported Platforms

Usage

```
available_df()
```

Value

A data frame with columns:

- year: character
- R.version: character; e.g., "3.5.3"
- bioc_version: character; Bioconductor version, e.g., "3.22"
- date: character; in format <yyyy>-<mm>-<dd>
- Linux/wsl: character; "supported", "unsupported", or "might work"
- Apple Silicon: character; "supported", "unsupported", "might work", or "supported (Rstudio broken)"
- Intel Mac: character; "supported", "unsupported", or "might work"

See Also

Other available versions: [available_dates\(\)](#), [available_r\(\)](#)

Examples

```
available_dates()
```

available_r	<i>List Available R Versions from the rstats-on-nix Fork of Nixpkgs</i>
-------------	---

Description

List Available R Versions from the rstats-on-nix Fork of Nixpkgs

Usage

```
available_r()
```

Value

A character vector containing the available R versions.

See Also

Other available versions: [available_dates\(\)](#), [available_df\(\)](#)

Examples

```
available_r()
```

ga_cachix

Build an Environment on GitHub Actions and Cache It on Cachix

Description

Build an Environment on GitHub Actions and Cache It on Cachix

Usage

```
ga_cachix(cache_name, path_default)
```

Arguments

cache_name	String, name of your cache.
path_default	String, relative path (from the root directory of your project) to the default.nix to build.

Details

This function puts a .yaml file inside the .github/workflows/ folders on the root of your project. This workflow file will use the projects default.nix file to generate the development environment on GitHub Actions and will then cache the created binaries in Cachix. Create a free account on Cachix to use this action. Refer to `vignette("binary-cache")` for detailed instructions. Make sure to give read and write permissions to the GitHub Actions bot.

Value

Nothing, copies file to a directory.

See Also

Other CI/CD: [tar_nix_ga\(\)](#)

Examples

```
## Not run:  
ga_cachix("my-cachix", path_default = "default.nix")  
  
## End(Not run)
```

make_launcher

Create a Startup Script to Launch an Editor Inside a Nix Shell

Description

Create a Startup Script to Launch an Editor Inside a Nix Shell

Usage

```
make_launcher(editor, project_path)
```

Arguments

editor	Character, the command to launch the editor. See the "Details" section below for more information.
project_path	Character, where to write the launcher, for example "/home/path/to/project". The file will thus be written to the file "/home/path/to/project/start-editor.sh". If the folder does not exist, it will be created.

Details

This function will write a launcher to start an IDE inside of a Nix shell. With a launcher, you only need to execute it instead of first having to drop into the shell using `nix-shell` and then type the command to run the IDE. You don't need this launcher if you use `direnv`; see `vignette("configuring-ide")` for more details.

Value

Nothing, writes a script.

Examples

```
available_dates()
```

nix_build

Invoke Shell Command nix-build from an R Session

Description

Invoke Shell Command `nix-build` from an R Session

Usage

```
nix_build(
  project_path = getwd(),
  message_type = c("simple", "quiet", "verbose"),
  args = NULL
)
```

Arguments

<code>project_path</code>	Path to the folder where the <code>default.nix</code> file resides.
<code>message_type</code>	Character vector with messaging type. Either "simple" (default), "quiet" for no messaging, or "verbose".
<code>args</code>	A character vector of additional arguments to be passed directly to the <code>nix-build</code> command. If the project directory (i.e. <code>project_path</code>) is not included in <code>args</code> , it will be appended automatically.

Details

This function is a wrapper for the `nix-build` command-line interface. Users can supply any flags supported by `nix-build` via the `args` parameter. If no custom arguments are provided, only the project directory is passed.

Value

Integer of the process ID (PID) of the `nix-build` shell command launched, if the `nix_build()` call is assigned to an R object. Otherwise, it will be returned invisibly.

See Also

Other Nix execution: [with_nix\(\)](#)

Examples

```
## Not run:
# Run nix-build with default arguments (project directory)
nix_build()

# Run nix-build with custom arguments
nix_build(args = c("--max-jobs", "2", "--quiet"))

## End(Not run)
```

renv2nix

Convert an `renv.lock` File to a Nix Expression

Description

Convert an `renv.lock` File to a Nix Expression

Usage

```
renv2nix(
  renv_lock_path = "renv.lock",
  project_path,
  return_rix_call = FALSE,
  method = c("fast", "accurate"),
  override_r_ver = NULL,
  ...
)
```

Arguments

renv_lock_path	Character, path of the renv.lock file, defaults to "renv.lock"
project_path	Character, where to write default.nix, for example "/home/path/to/project". The file will thus be written to the file "/home/path/to/project/default.nix". If the folder does not exist, it will be created.
return_rix_call	Logical, return the generated rix function call instead of evaluating it this is for debugging purposes, defaults to FALSE
method	Character, the method of generating a nix environment from an renv.lock file. "fast" is an inexact conversion which simply extracts the R version and a list of all the packages in an renv.lock file and adds them to the r_pkgs argument of rix(). This will use a snapshot of nixpkgs that should contain package versions that are not too different from the ones defined in the renv.lock file. For packages installed from GitHub or similar, an attempt is made to handle them and pass them to the git_pkgs argument of rix(). Currently defaults to "fast", "accurate" is not yet implemented.
override_r_ver	Character, defaults to NULL, override the R version defined in the renv.lock file with another version. This is especially useful if the renv.lock file lists a version of R not (yet) available through Nix, or if the R version included in the renv.lock is too old compared to the package versions. Can also be a date, check available_dates().
...	Arguments passed on to rix
system_pkgs	Vector of characters. List further software you wish to install that are not R packages such as command line applications for example. You can look for available software on the NixOS website https://search.nixos.org/packages?channel=unstable&from=0&size=50&sort=relevance&type=packages&query=
local_r_pkgs	Vector of characters, paths to local packages to install. These packages need to be in the .tar.gz or .zip formats and must be in the same folder as the generated "default.nix" file.
tex_pkgs	Vector of characters. A set of TeX packages to install. Use this if you need to compile .tex documents, or build PDF documents using Quarto. If you don't know which package to add, start by adding "amsmath". See the vignette("d2- installing-system-tools-and-texlive-packages-in-a-nix-environment") for more details.

`py_conf` List. A list containing two or three elements: `py_version`, `py_pkgs`, and optionally `py_src_dir`. `py_version` should be in the form "3.12" for Python 3.12, and `py_pkgs` should be an atomic vector of package names (e.g., `py_pkgs = c("polars", "plotnine", "great-tables")`). If Python packages are requested but `{reticulate}` is not in the list of R packages, the user will be warned that they may want to add it. When `py_conf` packages are requested, the `RETICULATE_PYTHON` environment variable is set to ensure the Nix environment does not use a system-wide Python installation. If you are developing a Python package, set `"mypackage/src"` or just `"src"`). This adds `PYTHONPATH` to the shell hook so your package can be imported without installation. This is the Nix equivalent of `pip install -e .` (editable install). Note: if `"uv"` is in `system_pkgs`, `LD_LIBRARY_PATH` is automatically configured for dynamic library loading (required by packages like `numpy`). You can also install packages from `git` or `PyPI` by adding `git_pkgs` (list of lists with `package_name`, `repo_url`, `commit`) and `pypi_pkgs` (vector of package names, optionally with version `name@version`) to the `py_conf` list.

`j1_conf` List. A list of two elements, `j1_version` and `j1_conf`. `j1_version` must be of the form "1.10" for Julia 1.10. Leave empty or use an empty string to use the latest version, or use `"lts"` for the long term support version. `j1_conf` must be an atomic vector of packages names, for example `j1_conf = c("TidierData", "TidierPlots")`.

`ide` Character, defaults to `"none"`. If you wish to use RStudio to work interactively use `"rstudio"` or `"rserver"` for the server version. Use `"code"` for Visual Studio Code or `"codium"` for Codium, or `"positron"` for Positron. You can also use `"radian"`, an interactive REPL. This will install a project-specific version of the chosen editor which will be different than the one already present in your system (if any). For other editors or if you want to use an editor already installed on your system (which will require some configuration to make it work seamlessly with Nix shells see the vignette(`"configuring-ide"`) for configuration examples), use `"none"`. Please be aware that VS Code and Positron are not free software. To facilitate their installation, `rix()` automatically enables a required setting without prompting the user for confirmation. See the "Details" section below for more information.

`overwrite` Logical, defaults to `FALSE`. If `TRUE`, overwrite the `default.nix` file in the specified path.

`print` Logical, defaults to `FALSE`. If `TRUE`, print `default.nix` to console.

`message_type` Character. Message type, defaults to `"simple"`, which gives minimal but sufficient feedback. Other values are currently `"quiet"`, which generates the files without message, and `"verbose"`, displays all the messages.

`shell_hook` Character of length 1, defaults to `NULL`. Commands added to the `shellHook` variable are executed when the Nix shell starts. So by default, using `nix-shell default.nix` will start a specific program, possibly with flags (separated by space), and/or do shell actions. You can for example use `shell_hook = R`, if you want to directly enter the declared Nix R session when dropping into the Nix shell.

Details

In order for this function to work properly, we recommend not running it inside the same folder as an existing {renv} project. Instead, run it from a new, empty directory which path you pass to `project_path`, and use `renv_lock_path` to point to the `renv.lock` file in the original {renv} folder. We recommend that you start from an empty folder to hold your new Nix project, and copy the `renv.lock` file only (not any of the other files and folders generated by {renv}) and then call `renv2nix()` there. For more details, see `vignette("renv2nix")`.

Value

Nothing, this function is called for its side effects only, unless `return_rix_call = TRUE` in which case an unevaluated call to `rix()` is returned

Examples

```
## Not run:
# if the lock file is in another folder
renv2nix(
  renv_lock_path = "path/to/original/renv_project/renv.lock",
  project_path = "path/to/rix_project"
)
# you could also copy the renv.lock file in the folder of the Nix
# project (don't copy any other files generated by `{renv}`)
renv2nix(
  renv_lock_path = "path/to/rix_project/renv.lock",
  project_path = "path/to/rix_project"
)

## End(Not run)
```

rix

Generate a Nix Expression That Builds a Reproducible Development Environment

Description

Generate a Nix Expression That Builds a Reproducible Development Environment

Usage

```
rix(
  r_ver = NULL,
  date = NULL,
  r_pkgs = NULL,
  system_pkgs = NULL,
  git_pkgs = NULL,
  local_r_pkgs = NULL,
```

```

tex_pkgs = NULL,
py_conf = NULL,
jl_conf = NULL,
ide = "none",
project_path,
overwrite = FALSE,
print = FALSE,
message_type = "simple",
shell_hook = NULL,
ignore_remotes_cache = FALSE
)

```

Arguments

<code>r_ver</code>	Character. The required R version, for example "4.0.0". You can check which R versions are available using <code>available_r()</code> , and for more details check <code>available_df()</code> . For reproducibility purposes, you can also provide a nixpkgs revision directly. For older versions of R, nix-build might fail with an error stating 'this derivation is not meant to be built'. In this case, simply drop into the shell with <code>nix-shell</code> instead of building it first. It is also possible to provide either "bleeding-edge" or "frozen-edge" if you need an environment with bleeding edge packages. Read more in the "Details" section below.
<code>date</code>	Character. Instead of providing <code>r_ver</code> , it is also possible to provide a date. This will build an environment containing R and R packages (and other dependencies) as of that date. You can check which dates are available with <code>available_dates()</code> . For more details about versions check <code>available_df()</code> .
<code>r_pkgs</code>	Vector of characters. List the required R packages for your analysis here.
<code>system_pkgs</code>	Vector of characters. List further software you wish to install that are not R packages such as command line applications for example. You can look for available software on the NixOS website https://search.nixos.org/packages?channel=unstable&from=0&size=50&sort=relevance&type=packages&query=
<code>git_pkgs</code>	List. A list of packages to install from Git. See details for more information.
<code>local_r_pkgs</code>	Vector of characters, paths to local packages to install. These packages need to be in the .tar.gz or .zip formats and must be in the same folder as the generated "default.nix" file.
<code>tex_pkgs</code>	Vector of characters. A set of TeX packages to install. Use this if you need to compile .tex documents, or build PDF documents using Quarto. If you don't know which package to add, start by adding "amsmath". See the vignette("d2-installing-system-tools-and-texlive-packages-in-a-nix-environment") for more details.
<code>py_conf</code>	List. A list containing two or three elements: <code>py_version</code> , <code>py_pkgs</code> , and optionally <code>py_src_dir</code> . <code>py_version</code> should be in the form "3.12" for Python 3.12, and <code>py_pkgs</code> should be an atomic vector of package names (e.g., <code>py_pkgs = c("polars", "plotnine", "great-tables")</code>). If Python packages are requested but {reticulate} is not in the list of R packages, the user will be warned that they may want to add it. When <code>py_conf</code> packages are requested,

the `RETICULATE_PYTHON` environment variable is set to ensure the Nix environment does not use a system-wide Python installation. If you are developing a Python package, set `"mypackage/src"` or just `"src"`). This adds `PYTHONPATH` to the shell hook so your package can be imported without installation. This is the Nix equivalent of `pip install -e .` (editable install). Note: if `"uv"` is in `system_pkgs`, `LD_LIBRARY_PATH` is automatically configured for dynamic library loading (required by packages like `numpy`). You can also install packages from git or PyPI by adding `git_pkgs` (list of lists with `package_name`, `repo_url`, `commit`) and `pypi_pkgs` (vector of package names, optionally with version `name@version`) to the `py_conf` list.

<code>jl_conf</code>	List. A list of two elements, <code>jl_version</code> and <code>jl_conf</code> . <code>jl_version</code> must be of the form <code>"1.10"</code> for Julia 1.10. Leave empty or use an empty string to use the latest version, or use <code>"lts"</code> for the long term support version. <code>jl_conf</code> must be an atomic vector of packages names, for example <code>jl_conf = c("TidierData", "TidierPlots")</code> .
<code>ide</code>	Character, defaults to <code>"none"</code> . If you wish to use RStudio to work interactively use <code>"rstudio"</code> or <code>"rserver"</code> for the server version. Use <code>"code"</code> for Visual Studio Code or <code>"codium"</code> for Codium, or <code>"positron"</code> for Positron. You can also use <code>"radian"</code> , an interactive REPL. This will install a project-specific version of the chosen editor which will be different than the one already present in your system (if any). For other editors or if you want to use an editor already installed on your system (which will require some configuration to make it work seamlessly with Nix shells see the vignette(<code>"configuring-ide"</code>) for configuration examples), use <code>"none"</code> . Please be aware that VS Code and Positron are not free software. To facilitate their installation, <code>rix()</code> automatically enables a required setting without prompting the user for confirmation. See the "Details" section below for more information.
<code>project_path</code>	Character, where to write <code>default.nix</code> , for example <code>"/home/path/to/project"</code> . The file will thus be written to the file <code>"/home/path/to/project/default.nix"</code> . If the folder does not exist, it will be created.
<code>overwrite</code>	Logical, defaults to <code>FALSE</code> . If <code>TRUE</code> , overwrite the <code>default.nix</code> file in the specified path.
<code>print</code>	Logical, defaults to <code>FALSE</code> . If <code>TRUE</code> , print <code>default.nix</code> to console.
<code>message_type</code>	Character. Message type, defaults to <code>"simple"</code> , which gives minimal but sufficient feedback. Other values are currently <code>"quiet"</code> , which generates the files without message, and <code>"verbose"</code> , displays all the messages.
<code>shell_hook</code>	Character of length 1, defaults to <code>NULL</code> . Commands added to the <code>shellHook</code> variable are executed when the Nix shell starts. So by default, using <code>nix-shell default.nix</code> will start a specific program, possibly with flags (separated by space), and/or do shell actions. You can for example use <code>shell_hook = R</code> , if you want to directly enter the declared Nix R session when dropping into the Nix shell.
<code>ignore_remotes_cache</code>	Logical, defaults to <code>FALSE</code> . This variable is only needed when adding packages from GitHub with remote dependencies, it can be ignored otherwise. If <code>TRUE</code> , the cache of already processed GitHub remotes will be ignored and all packages will be processed. If <code>FALSE</code> , the cache will be used to skip already processed

packages, which makes use of fewer API calls. Setting this argument to TRUE can be useful for debugging.

Details

This function will write a `default.nix` and an `.Rprofile` in the chosen path. Using the Nix package manager, it is then possible to build a reproducible development environment using the `nix-build` command in the path. This environment will contain the chosen version of R and packages, and will not interfere with any other installed version (via Nix or not) on your machine. Every dependency, including both R package dependencies but also system dependencies like compilers will get installed as well in that environment.

It is possible to use environments built with Nix interactively, either from the terminal, or using an interface such as RStudio. If you want to use RStudio, set the `ide` argument to `"rstudio"`. Please be aware that for macOS, RStudio is only available starting from R version 4.4.3 or from the 2025-02-28. As such, you may want to use another editor on macOS if you need to use an environment with an older version of R. To use Visual Studio Code (or Codium), set the `ide` argument to `"code"` or `"codium"` respectively, which will add the `{languageserver}` R package to the list of R packages to be installed by Nix in that environment. It is also possible to use Positron by setting the `ide` argument to `"positron"`. Setting the `ide` argument to an editor will install it from Nix, meaning that each of your projects can have a dedicated IDE (or IDE version). `"radian"` and `"rserver"` are also options.

Instead of using Nix to install an IDE, you can also simply use the one you have already installed on your system, with the exception of RStudio which must be managed by Nix to "see" Nix environments. Positron must also be heavily configured to work with Nix shells, so we recommend installing it using Nix. To use an editor that you already have installed on your system, set `ide = "none"` and refer to the vignette(`"configuring-ide"`) for more details on how to set up your editor to work with Nix shells.

Packages to install from GitHub, GitLab, or other custom Git hosts (Forgejo, Gitea, cgit, etc.) must be provided in a list of 3 elements: `"package_name"`, `"repo_url"` and `"commit"`. To install several packages, provide a list of lists of these 3 elements, one per package to install. It is also possible to install old versions of packages by specifying a version. For example, to install the latest version of `{AER}` but an old version of `{ggplot2}`, you could write: `r_pkgs = c("AER", "ggplot2@2.2.1")`. Note however that doing this could result in dependency hell, because an older version of a package might need older versions of its dependencies, but other packages might need more recent versions of the same dependencies. If instead you want to use an environment as it would have looked at the time of `{ggplot2}`'s version 2.2.1 release, then use the Nix revision closest to that date, by setting `r_ver = "3.1.0"`, which was the version of R current at the time. This ensures that Nix builds a completely coherent environment. For security purposes, users that wish to install packages from GitHub, GitLab, or other Git hosts, or from the CRAN archives must provide a security hash for each package. `{rix}` automatically precomputes this hash for the source directory of R packages from Git hosts or from the CRAN archives, to make sure the expected trusted sources that match the precomputed hashes in the `default.nix` are downloaded, but only if Nix is installed. If you need to generate an expression with such packages, but are working on a system where you can't install Nix, consider generating the expression using a continuous integration service, such as GitHub Actions.

For **private repositories**, an optional fourth element `"private"` can be set to TRUE. When `private = TRUE`, you must provide an SSH URL (e.g., `git@github.com:org/repo.git`) instead of an HTTPS URL. The package will be fetched using `builtins.fetchGit` which uses your SSH keys

for authentication. Note that this has tradeoffs: it works seamlessly with SSH keys, but cannot be cached in Nix binary caches and may not work in pure Nix evaluation mode or some CI/CD environments. See the vignette("installing-r-packages") for more details on installing from private repositories.

Note that installing packages from Git or old versions using the "@" notation or local packages, does not leverage Nix's capabilities for dependency solving. As such, you might have trouble installing these packages. If that is the case, open an issue on {rix}'s GitHub repository.

If GitHub packages have dependencies on GitHub as well, {rix} will attempt to generate the correct expression, but we highly recommend you read the vignette("remote-dependencies") Vignette.

By default, the Nix shell will be configured with "en_US.UTF-8" for the relevant locale variables (LANG, LC_ALL, LC_TIME, LC_MONETARY, LC_PAPER, LC_MEASUREMENT). This is done to ensure locale reproducibility by default in Nix environments created with rix(). If there are good reasons to not stick to the default, you can set your preferred locale variables via options(rix.nix_locale_variables = list(LANG = "C" and the aforementioned locale variable names.

It is possible to use "bleeding-edge" or "frozen-edge" as the value for the r_ver argument. This will create an environment with the very latest R packages. "bleeding-edge" means that every time you will build the environment, the packages will get updated. This is especially useful for environments that need to be constantly updated, for example when developing a package. In contrast, "frozen-edge" will create an environment that will remain stable at build time. So if you create a default.nix file using "bleeding-edge", each time you build it using nix-build that environment will be up-to-date. With "frozen-edge" that environment will be up-to-date on the date that the default.nix will be generated, and then each subsequent call to nix-build will result in the same environment. "bioc-devel" is the same as "bleeding-edge", but also adds the development version of Bioconductor. "r-devel" is the same as bleeding edge, but with the R development version instead of the latest stable version and "r-devel-bioc-devel" is the same as "r-devel" but with Bioconductor on the development version. We highly recommend you read the vignette titled "z - Advanced topic: Understanding the rPackages set release cycle and using bleeding edge packages".

Value

Nothing, this function only has the side-effect of writing two files: default.nix and .Rprofile in the working directory. default.nix contains a Nix expression to build a reproducible environment using the Nix package manager, and .Rprofile ensures that a running R session from a Nix environment cannot access local libraries, nor install packages using install.packages() (nor remove nor update them).

See Also

Other core functions: [rix_init\(\)](#)

Examples

```
## Not run:
# Build an environment with the latest version of R available from Nixpkgs
# and the dplyr and ggplot2 packages
rix(
  r_ver = "latest-upstream",
```

```

r_pkgs = c("dplyr", "ggplot2"),
system_pkgs = NULL,
git_pkgs = NULL,
local_r_pkgs = NULL,
ide = "code",
project_path = path_default_nix,
overwrite = TRUE,
print = TRUE,
message_type = "simple",
shell_hook = NULL,
ignore_remotes_cache = FALSE
)

## End(Not run)

```

rix_init	<i>Initiate and Maintain an Isolated, Project-Specific, and Runtime-Pure R Setup via Nix.</i>
----------	---

Description

Creates an isolated project folder for a Nix-R configuration. `rix::rix_init()` also adds, appends, or updates with or without backup a custom `.Rprofile` file with code that initializes a startup R environment without system's user libraries within a Nix software environment. Instead, it restricts search paths to load R packages exclusively from the Nix store. Additionally, it makes Nix utilities like `nix-shell` available to run system commands from the system's RStudio R session, for both Linux and macOS.

Usage

```

rix_init(
  project_path,
  rprofile_action = c("create_missing", "create_backup", "overwrite", "append"),
  message_type = c("simple", "quiet", "verbose")
)

```

Arguments

<code>project_path</code>	Character with the folder path to the isolated nix-R project. If the folder does not exist yet, it will be created.
<code>rprofile_action</code>	Character. Action to take with <code>.Rprofile</code> file destined for <code>project_path</code> folder. Possible values include <code>"create_missing"</code> , which only writes <code>.Rprofile</code> if it does not yet exist (otherwise does nothing) - this is the action set when using <code>rix()</code> - ; <code>"create_backup"</code> , which copies the existing <code>.Rprofile</code> to a new backup file, generating names with POSIXct-derived strings that include the time zone information. A new <code>.Rprofile</code> file will be written with default code from <code>rix::rix_init()</code> ; <code>"overwrite"</code> overwrites the <code>.Rprofile</code> file if it does

	exist; "append" appends the existing file with code that is tailored to an isolated Nix-R project setup.
message_type	Character. Message type, defaults to "simple", which gives minimal but sufficient feedback. Other values are currently "quiet", which writes .Rprofile without message, and "verbose", which displays the mechanisms implemented to achieve fully controlled R project environments in Nix.

Details

Enhancement of computational reproducibility for Nix-R environments:

The primary goal of `rix::rix_init()` is to enhance the computational reproducibility of Nix-R environments during runtime. Concretely, if you already have a system or user library of R packages (if you have R installed through the usual means for your operating system), using `rix::rix_init()` will prevent Nix-R environments to load packages from the user library which would cause issues. Notably, no restart is required as environmental variables are set in the current session, in addition to writing an .Rprofile file. This is particularly useful to make `with_nix()` evaluate custom R functions from any "Nix-to-Nix" or "System-to-Nix" R setups. It introduces two side-effects that take effect both in a current or later R session setup:

1. **Adjusting R_LIBS_USER path:** By default, the first path of `R_LIBS_USER` points to the user library outside the Nix store (see also `base::.libPaths()`). This creates friction and potential impurity as R packages from the system's R user library are loaded. While this feature can be useful for interactively testing an R package in a Nix environment before adding it to a .nix configuration, it can have undesired effects if not managed carefully. A major drawback is that all R packages in the `R_LIBS_USER` location need to be cleaned to avoid loading packages outside the Nix configuration. Issues, especially on macOS, may arise due to segmentation faults or incompatible linked system libraries. These problems can also occur if one of the (reverse) dependencies of an R package is loaded along the process.
2. **Make Nix commands available when running system commands from RStudio:** In a host RStudio session not launched via Nix (`nix-shell`), the environmental variables from `~/.zshrc` or `~/.bashrc` may not be inherited. Consequently, Nix command line interfaces like `nix-shell` might not be found. The .Rprofile code written by `rix::rix_init()` ensures that Nix command line programs are accessible by adding the path of the "bin" directory of the default Nix profile, `"/nix/var/nix/profiles/default/bin"`, to the `PATH` variable in an RStudio R session.

These side effects are particularly recommended when working in flexible R environments, especially for users who want to maintain both the system's native R setup and utilize Nix expressions for reproducible development environments. This init configuration is considered pivotal to enhance the adoption of Nix in the R community, particularly until RStudio in Nixpkgs is packaged for macOS. We recommend calling `rix::rix_init()` prior to comparing R code ran between two software environments with `rix::with_nix()`.

`rix::rix_init()` is called automatically by `rix::rix()` when generating a default.nix file, and when called by `rix::rix()` will only add the .Rprofile if none exists. In case you have a custom .Rprofile that you wish to keep using, but also want to benefit from what `rix_init()` offers, manually call it and set the `rprofile_action` to "append".

Value

Nothing, this function only has the side-effect of writing a file called ".Rprofile" to the specified path.

See Also

[with_nix\(\)](#)

Other core functions: [rix\(\)](#)

Examples

```
## Not run:
# create an isolated, runtime-pure R setup via Nix
project_path <- "./sub_shell"
if (!dir.exists(project_path)) dir.create(project_path)
rix_init(
  project_path = project_path,
  rprofile_action = "create_missing",
  message_type = c("simple")
)

## End(Not run)
```

 setup_cachix

Configure the rstats-on-nix Binary Cache

Description

Configure the rstats-on-nix Binary Cache

Usage

```
setup_cachix(nix_conf_path = "~/config/nix")
```

Arguments

`nix_conf_path` Character, path to folder containing 'nix.conf' file. Defaults to "~/config/nix".

Details

This function edits ~/config/nix/nix.conf to add the rstats-on-nix public cache as a substituter. The rstats-on-nix public cache, hosted on Cachix, contains many prebuild binaries of R and R packages for x86_64 Linux and macOS (Intel architectures for packages released before 2021 and Apple Silicon from 2021 onwards). This function automatically performs a backup of ~/config/nix/nix.conf, or creates one if there is no nix.conf file.

This is the recommended approach for configuring the cache, as it works with both standard Nix installations and Determinate Nix installations. After running this function, you also need to add yourself to trusted-users so Nix allows you to use the cache. Run one of:

- **Linux:** `echo "trusted-users = root $USER" | sudo tee -a /etc/nix/nix.custom.conf && sudo systemctl re`
- **macOS:** `echo "trusted-users = root $USER" | sudo tee -a /etc/nix/nix.custom.conf && sudo launchctl k`

If you see warnings like "ignoring untrusted substituter", this means the trusted-users configuration is not in place.

NixOS users: This function does not work on NixOS because the Nix configuration is managed declaratively. Instead, configure the cache in your system configuration. Without Home Manager, add this to your configuration.nix:

```
nix.settings = {
  substituters = [
    "https://cache.nixos.org"
    "https://rstats-on-nix.cachix.org"
  ];
  trusted-public-keys = [
    "cache.nixos.org-1:6NCHdD59X431o0gWypbMrAURkbJ16ZPMQFGspcDShjY="
    "rstats-on-nix.cachix.org-1:vdiiVgocg6WeJrODIqdprZRURhi1JzhBnXv7aWI6+F0="
  ];
};
```

With Home Manager, add this to your home configuration:

```
nix.settings = {
  substituters = [
    "https://rstats-on-nix.cachix.org"
  ];
  trusted-public-keys = [
    "rstats-on-nix.cachix.org-1:vdiiVgocg6WeJrODIqdprZRURhi1JzhBnXv7aWI6+F0="
  ];
};
```

Other use cases include: if you somehow mess up `~/.config/nix/nix.conf` and need to generate a new one from scratch, or if you're using Nix inside Docker, write a `RUN Rscript -e 'rix::setup_cachix()'` statement to configure the cache there. Because Docker runs using root by default no need to install the cachix client to configure the cache, running `setup_cachix()` is enough. See the 'z - Advanced topic: Using Nix inside Docker' vignette for more details.

Value

Nothing; changes a file in the user's home directory.

Examples

```
## Not run:
setup_cachix()

## End(Not run)
```

tar_nix_ga

*Run a Targets Pipeline on GitHub Actions***Description**

Run a Targets Pipeline on GitHub Actions

Usage

```
tar_nix_ga()
```

Details

This function puts a .yaml file inside the .github/workflows/ folders on the root of your project. This workflow file will use the projects default .nix file to generate the development environment on GitHub Actions and will then run the projects {targets} pipeline. Make sure to give read and write permissions to the GitHub Actions bot.

Value

Nothing, copies file to a directory.

See Also

Other CI/CD: [ga_cachix\(\)](#)

Examples

```
## Not run:
tar_nix_ga()

## End(Not run)
```

with_nix

*Evaluate Function in R or Shell Command via nix-shell Environment***Description**

This function needs an installation of Nix. with_nix() has two effects to run code in isolated and reproducible environments.

1. Evaluate a function in R or a shell command via the nix-shell environment (Nix expression for custom software libraries; involving pinned versions of R and R packages via Nixpkgs)
2. If no error, return the result object of expr in with_nix() into the current R session.

Usage

```
with_nix(
  expr,
  program = c("R", "shell"),
  project_path = ".",
  message_type = c("simple", "quiet", "verbose")
)
```

Arguments

expr	Single R function or call, or character vector of length one with shell command and possibly options (flags) of the command to be invoked. For program = R, you can both use a named or an anonymous function. The function provided in expr should not evaluate when you pass arguments, hence you need to wrap your function call like function() your_fun(arg_a = "a", arg_b = "b"), to avoid evaluation and make sure expr is a function (see details and examples).
program	String stating where to evaluate the expression. Either "R", the default, or "shell". where = "R" will evaluate the expression via RScript and where = "shell" will run the system command in nix-shell.
project_path	Path to the folder where the default.nix file resides. The default is ".", which is the working directory in the current R session. This approach also useful when you have different subfolders with separate software environments defined in different default.nix files.
message_type	String how detailed output is. Currently, there is either "simple" (default), "quiet" or "verbose", which shows the script that runs via nix-shell.

Details

with_nix() gives you the power of evaluating a main function expr and its function call stack that are defined in the current R session in an encapsulated nix-R session defined by Nix expression (default.nix), which is located in at a distinct project path (project_path).

with_nix() is very convenient because it gives direct code feedback in read-eval-print-loop style, which gives a direct interface to the very reproducible infrastructure-as-code approach offered by Nix and Nixpkgs. You don't need extra efforts such as setting up DevOps tooling like Docker and domain specific tools like {renv} to control complex software environments in R and any other language. It is for example useful for the following purposes.

1. test compatibility of custom R code and software/package dependencies in development and production environments
2. directly stream outputs (returned objects), messages and errors from any command line tool offered in Nixpkgs into an R session.
3. Test if evolving R packages change their behavior for given unchanged R code, and whether they give identical results or not.

with_nix() can evaluate both R code from a nix-R session within another nix-R session, and also from a host R session (i.e., on macOS or Linux) within a specific nix-R session. This feature is

useful for testing the reproducibility and compatibility of given code across different software environments. If testing of different sets of environments is necessary, you can easily do so by providing Nix expressions in custom `.nix` or `default.nix` files in different subfolders of the project.

`rix_init()` is run automatically to generate a custom `.Rprofile` file for the subshell in `project_dir`. The defaults in that file ensure that only R packages from the Nix store, that are defined in the subshell `.nix` file are loaded and system's libraries are excluded.

To do its job, `with_nix()` heavily relies on patterns that manipulate language expressions (aka computing on the language) offered in base R as well as the `{codetools}` package by Luke Tierney.

Some of the key steps that are done behind the scene:

1. recursively find, classify, and export global objects (globals) in the call stack of `expr` as well as propagate R package environments found.
2. Serialize (save to disk) and deserialize (read from disk) dependent data structures as `.Rds` with necessary function arguments provided, any relevant globals in the call stack, packages, and `expr` outputs returned in a temporary directory.
3. Use pure `nix-shell` environments to execute a R code script reconstructed catching expressions with quoting; it is launched by commands like this via `{sys}` by Jeroen Ooms: `nix-shell --pure --run "Rscript --vanilla"`.

Value

- if `program = "R"`, R object returned by function given in `expr` when evaluated via the R environment in `nix-shell` defined by Nix expression.
- if `program = "shell"`, list with the following elements:
 - `status`: exit code
 - `stdout`: character vector with standard output
 - `stderr`: character vector with standard error of `expr` command sent to a command line interface provided by a Nix package.

See Also

Other Nix execution: [nix_build\(\)](#)

Examples

```
## Not run:
# create an isolated, runtime-pure R setup via Nix
project_path <- "./sub_shell"
rix_init(
  project_path = project_path,
  rprofile_action = "create_missing"
)
# generate nix environment in `default.nix`
rix(
  r_ver = "4.2.0",
  project_path = project_path
)
# evaluate function in Nix-R environment via `nix-shell` and `Rscript`,
```

```
# stream messages, and bring output back to current R session
out <- with_nix(
  expr = function(mtcars) nrow(mtcars),
  program = "R", project_path = project_path,
  message_type = "simple"
)

# There no limit in the complexity of function call stacks that `with_nix()`
# can possibly handle; however, `expr` should not evaluate and
# needs to be a function for `program = "R"`. If you want to pass the
# a function with arguments, you can do like this
get_sample <- function(seed, n) {
  set.seed(seed)
  out <- sample(seq(1, 10), n)
  return(out)
}

out <- with_nix(
  expr = function() get_sample(seed = 1234, n = 5),
  program = "R",
  project_path = ".",
  message_type = "simple"
)

## You can also attach packages with `library()` calls in the current R
## session, which will be exported to the nix-R session.
## Other option: running system commands through `nix-shell` environment.

## End(Not run)
```

Index

- * **CI/CD**
 - ga_cachix, 4
 - tar_nix_ga, 18
- * **Nix execution**
 - nix_build, 5
 - with_nix, 18
- * **available versions**
 - available_dates, 2
 - available_df, 3
 - available_r, 3
- * **core functions**
 - rix, 9
 - rix_init, 14

available_dates, 2

available_dates(), 3, 4

available_df, 3

available_df(), 2, 4

available_r, 3

available_r(), 2, 3

base::libPaths(), 15

ga_cachix, 4

ga_cachix(), 18

make_launcher, 5

nix_build, 5

nix_build(), 20

renv2nix, 6

rix, 7, 9

rix(), 16

rix_init, 14

rix_init(), 13

setup_cachix, 16

tar_nix_ga, 18

tar_nix_ga(), 4

with_nix, 18

with_nix(), 6, 15, 16