

Package: rnaturalearth (via r-universe)

August 29, 2024

Title World Map Data from Natural Earth

Version 1.0.1.9000

Description Facilitates mapping by making natural earth map data from
<<https://www.naturalearthdata.com/>> more easily available to R
users.

License MIT + file LICENSE

LazyData true

LazyDataCompression xz

Encoding UTF-8

URL <https://docs.ropensci.org/rnaturalearth/>,
<https://github.com/ropensci/rnaturalearth>,
<https://docs.ropensci.org/rnaturalearthhires/>

BugReports <https://github.com/ropensci/rnaturalearth/issues>

Additional_repositories <http://packages.ropensci.org>

Depends R (>= 3.1.1)

Imports httr (>= 1.1.0), jsonlite, sf (>= 0.3-4), terra, utils (>= 3.2.3)

Suggests devtools (>= 1.10.0), dplyr, ggplot2, ggrepel, knitr (>= 1.12.3), lifecycle (>= 1.0.3), pbapply, purrr, rlang, rmarkdown, rnaturalearthdata (>= 1.0.0), rnaturalearthhires (>= 1.0.0), testthat (>= 0.9.1), tmap

Config/Needs/website ropensci/rnaturalearthhires

VignetteBuilder knitr

RoxygenNote 7.2.3

Repository <https://ropensci.r-universe.dev>

RemoteUrl <https://github.com/ropensci/rnaturalearth>

RemoteRef master

RemoteSha 137dd1931f61139d7d586040321d697344e842d3

Contents

check_data_exist	2
check_rnaturalearthdata	3
check_rnaturalearthhires	3
check_scale	4
convert_spatial_class	4
countries	5
df_layers_cultural	6
df_layers_physical	6
get_data	7
install_rnaturalearthdata	8
install_rnaturalearthhires	8
ne_coastline	9
ne_countries	10
ne_download	11
ne_file_name	13
ne_find_vector_data	14
ne_load	15
ne_states	16
Index	18

check_data_exist	<i>check whether the requested data exist on Natural Earth</i>
------------------	--

Description

checks from a list dependent on type, category and scale. If it returns FALSE the data may still exist on the website. Doesn't yet do checking on raster names because I found the naming convention too tricky.

Usage

```
check_data_exist(  
  scale = 110,  
  type,  
  category = c("cultural", "physical", "raster")  
)
```

Arguments

scale	The scale of map to return, one of '110', '50', '10' or 'small', 'medium', 'large'.
type	type of natural earth file to download one of 'countries', 'map_units', 'map_subunits', 'sovereignty', 'states' OR the portion of any natural earth vector url after the scale and before the . e.g. for 'ne_50m_urban_areas.zip' this would be 'urban_areas' OR the raster filename e.g. for 'MSR_50M.zip' this would be 'MSR_50M'
category	one of natural earth categories : 'cultural', 'physical', 'raster'

Details

Note that the filename of the requested object will be returned if 'load = FALSE'.

Value

TRUE or FALSE

See Also

[ne_load](#), pre-downloaded data are available using [ne_countries](#), [ne_states](#). Other geographic data are available in the raster package : [getData](#).

Examples

```
check_data_exist(scale = 110, category = "cultural", type = "countries")

# Type not in list for this category
check_data_exist(scale = 110, category = "physical", type = "airports")

# Type in list but scale shows FALSE
check_data_exist(scale = 110, category = "cultural", type = "airports")
```

`check_rnaturalearthdata`

Check whether to install rnaturalearthdata and install if necessary

Description

If the rnaturalearthdata package is not installed, install it from GitHub using devtools. If it is not up to date, reinstall it.

Usage

```
check_rnaturalearthdata()
```

`check_rnaturalearth hires`

Check whether to install rnaturalearth hires and install if necessary

Description

If the rnaturalearth hires package is not installed, install it from GitHub using devtools. If it is not up to date, reinstall it.

Usage

```
check_rnaturalearth hires()
```

check_scale	<i>check that this scale is present in Natural Earth</i>
-------------	--

Description

check name or numeric scale representations, return numeric one

Usage

```
check_scale(x)
```

Arguments

x	scale of map to return, one of 110, 50, 10 or 'small', 'medium', 'large'
---	--

Value

integer scale of map

convert_spatial_class	<i>Convert from/to sf/sv objects</i>
-----------------------	--------------------------------------

Description

returns downloaded data as a spatial object or the filename if load=FALSE. if destdir is specified the data can be reloaded in a later R session using [ne_load](#) with the same arguments.

Usage

```
convert_spatial_class(x, returnclass = c("sf", "sv"))
```

Arguments

x	Object to be converted
returnclass	A string determining the spatial object to return. Either "sf" for for simple feature (from 'sf', the default) or "sv" for a 'SpatVector' (from 'terra').

Details

Note that the filename of the requested object will be returned if 'load = FALSE'.

Value

Object of class "sf" or "sv"

See Also

[ne_load](#), pre-downloaded data are available using [ne_countries](#), [ne_states](#). Other geographic data are available in the raster package : [getData](#).

Examples

```
## Not run:
spdf_world <- ne_download(scale = 110, type = "countries")

plot(spdf_world)
plot(ne_download(type = "populated_places"))

# reloading from the saved file in the same session with same arguments

spdf_world2 <- ne_load(scale = 110, type = "countries")

# download followed by load from specified directory will work across sessions
spdf_world <- ne_download(scale = 110, type = "countries", destdir = getwd())
spdf_world2 <- ne_load(scale = 110, type = "countries", destdir = getwd())

# for raster, here an example with Manual Shaded Relief (MSR) download & load

rst <- ne_download(scale = 50, type = "MSR_50M", category = "raster", destdir = getwd())

# load after having downloaded
rst <- ne_load(
  scale = 50, type = "MSR_50M", category = "raster", destdir =
    getwd()
)

# plot
library(terra)
terra::plot(rst)
# end dontrun

## End(Not run)
```

countries

world country polygons from Natural Earth

Description

at 1:110m scale (small). Other data and resolutions are in the packages [rnaturalearthdata](#) and [rnaturalearthhires](#).

Usage

```
countries110
```

Format

A sf object.
An object of class sf (inherits from data.frame) with 177 rows and 169 columns.

Slots

data A data frame with country attributes.

Source

https://www.naturalearthdata.com/http://www.naturalearthdata.com/download/10m/cultural/ne_10m_admin_0_countries.zip

df_layers_cultural	<i>list of cultural layers available from Natural Earth</i>
--------------------	---

Description

list of cultural layers available from Natural Earth

Usage

df_layers_cultural

Format

A DataFrame
An object of class data.frame with 43 rows and 4 columns.

df_layers_physical	<i>list of physical layers available from Natural Earth</i>
--------------------	---

Description

list of physical layers available from Natural Earth

Usage

df_layers_physical

Format

A DataFrame
An object of class data.frame with 29 rows and 4 columns.

get_data	<i>Get data from within the package</i>
----------	---

Description

returns world country polygons at a specified scale, used by `ne_countries()`

Usage

```
get_data(
  scale = 110,
  type = c("countries", "map_units", "sovereignty", "tiny_countries")
)
```

Arguments

scale	The scale of map to return, one of '110', '50', '10' or 'small', 'medium', 'large'.
type	country type, one of 'countries', 'map_units', 'sovereignty', 'tiny_countries'

Details

Note that the filename of the requested object will be returned if 'load = FALSE'.

Value

A sf object.

See Also

[ne_load](#), pre-downloaded data are available using [ne_countries](#), [ne_states](#). Other geographic data are available in the raster package : [getData](#).

Examples

```
## Not run:
spdf_world <- ne_download(scale = 110, type = "countries")

plot(spdf_world)
plot(ne_download(type = "populated_places"))

# reloading from the saved file in the same session with same arguments

spdf_world2 <- ne_load(scale = 110, type = "countries")

# download followed by load from specified directory will work across sessions
spdf_world <- ne_download(scale = 110, type = "countries", destdir = getwd())
spdf_world2 <- ne_load(scale = 110, type = "countries", destdir = getwd())

# for raster, here an example with Manual Shaded Relief (MSR) download & load
```

```
rst <- ne_download(scale = 50, type = "MSR_50M", category = "raster", destdir = getwd())

# load after having downloaded
rst <- ne_load(
  scale = 50, type = "MSR_50M", category = "raster", destdir =
    getwd()
)

# plot
library(terra)
terra::plot(rst)
# end dontrun

## End(Not run)
```

install_rnaturalearthdata

Install the naturalearthdata package after checking with the user

Description

Install the naturalearthdata package after checking with the user

Usage

```
install_rnaturalearthdata()
```

install_rnaturalearthhires

Install the naturalearthhires package after checking with the user

Description

Install the naturalearthhires package after checking with the user

Usage

```
install_rnaturalearthhires()
```

ne_coastline	<i>Get natural earth world coastline</i>
--------------	--

Description

returns world coastline at specified scale

Usage

```
ne_coastline(scale = 110, returnclass = c("sf", "sv"))
```

Arguments

scale	The scale of map to return, one of '110', '50', '10' or 'small', 'medium', 'large'.
returnclass	A string determining the spatial object to return. Either "sf" for for simple feature (from 'sf', the default) or "sv" for a 'SpatVector' (from 'terra').

Details

Note that the filename of the requested object will be returned if 'load = FALSE'.

Value

An object of class 'sf' for simple feature (from 'sf', the default) or 'SpatVector' (from 'terra').

See Also

[ne_load](#), pre-downloaded data are available using [ne_countries](#), [ne_states](#). Other geographic data are available in the raster package : [getData](#).

Examples

```
if (requireNamespace("rnaturalearthdata")) {  
  coast <- ne_coastline()  
  plot(coast)  
}
```

ne_countries

Get natural earth world country polygons

Description

returns world country polygons at a specified scale, or points of tiny_countries

Usage

```
ne_countries(
  scale = 110,
  type = "countries",
  continent = NULL,
  country = NULL,
  geounit = NULL,
  sovereignty = NULL,
  returnclass = c("sf", "sv")
)
```

Arguments

scale	The scale of map to return, one of '110', '50', '10' or 'small', 'medium', 'large'.
type	country type, one of 'countries', 'map_units', 'sovereignty', 'tiny_countries'
continent	a character vector of continent names to get countries from.
country	a character vector of country names.
geounit	a character vector of geounit names.
sovereignty	a character vector of sovereignty names.
returnclass	A string determining the spatial object to return. Either "sf" for for simple feature (from 'sf', the default) or "sv" for a 'SpatVector' (from 'terra').

Details

Note that the filename of the requested object will be returned if 'load = FALSE'.

Value

An object of class 'sf' for simple feature (from 'sf', the default) or 'SpatVector' (from 'terra').

See Also

[ne_load](#), pre-downloaded data are available using [ne_countries](#), [ne_states](#). Other geographic data are available in the raster package : [getData](#).

Examples

```
world <- ne_countries()
africa <- ne_countries(continent = "africa")
france <- ne_countries(country = "france")

plot(world$geometry)
plot(africa$geometry)
plot(france$geometry)

# get as SpatVector
world <- ne_countries(returnclass = "sv")
terra::plot(world)

tiny_countries <- ne_countries(type = "tiny_countries", scale = 50)
plot(tiny_countries)
```

ne_download

Download data from Natural Earth and (optionally) read into R

Description

returns downloaded data as a spatial object or the filename if load=FALSE. if destdir is specified the data can be reloaded in a later R session using [ne_load](#) with the same arguments.

Usage

```
ne_download(
  scale = 110,
  type = "countries",
  category = c("cultural", "physical", "raster"),
  destdir = tempdir(),
  load = TRUE,
  returnclass = c("sf", "sv")
)
```

Arguments

scale	The scale of map to return, one of '110', '50', '10' or 'small', 'medium', 'large'.
type	type of natural earth file to download one of 'countries', 'map_units', 'map_subunits', 'sovereignty', 'states' OR the portion of any natural earth vector url after the scale and before the . e.g. for 'ne_50m_urban_areas.zip' this would be 'urban_areas'. See Details. OR the raster filename e.g. for 'MSR_50M.zip' this would be 'MSR_50M'
category	one of natural earth categories : 'cultural', 'physical', 'raster'
destdir	where to save files, defaults to tempdir(), getwd() is also possible.

load	'TRUE' load the spatial object into R, 'FALSE' return the filename of the downloaded object.
returnclass	A string determining the spatial object to return. Either "sf" for for simple feature (from 'sf', the default) or "sv" for a 'SpatVector' (from 'terra').

Details

Note that the filename of the requested object will be returned if 'load = FALSE'.

Value

An object of class 'sf' for simple feature (from 'sf', the default) or 'SpatVector' (from 'terra').

See Also

[ne_load](#), pre-downloaded data are available using [ne_countries](#), [ne_states](#). Other geographic data are available in the raster package : [getData](#).

Examples

```
## Not run:
spdf_world <- ne_download(scale = 110, type = "countries")

plot(spdf_world)
plot(ne_download(type = "populated_places"))

# reloading from the saved file in the same session with same arguments

spdf_world2 <- ne_load(scale = 110, type = "countries")

# download followed by load from specified directory will work across sessions
spdf_world <- ne_download(scale = 110, type = "countries", destdir = getwd())
spdf_world2 <- ne_load(scale = 110, type = "countries", destdir = getwd())

# for raster, here an example with Manual Shaded Relief (MSR) download & load

rst <- ne_download(scale = 50, type = "MSR_50M", category = "raster", destdir = getwd())

# load after having downloaded
rst <- ne_load(
  scale = 50, type = "MSR_50M", category = "raster", destdir =
    getwd()
)

# plot
library(terra)
terra::plot(rst)
# end dontrun

## End(Not run)
```

ne_file_name	<i>return a natural earth filename based on arguments</i>
--------------	---

Description

returns a string that can then be used to download the file.

Usage

```
ne_file_name(
  scale = 110,
  type = "countries",
  category = c("cultural", "physical", "raster"),
  full_url = FALSE
)
```

Arguments

scale	The scale of map to return, one of '110', '50', '10' or 'small', 'medium', 'large'.
type	type of natural earth file to download one of 'countries', 'map_units', 'map_subunits', 'sovereignty', 'states' OR the portion of any natural earth vector url after the scale and before the . e.g. for 'ne_50m_urban_areas.zip' this would be 'urban_areas' OR the raster filename e.g. for 'MSR_50M.zip' this would be 'MSR_50M'
category	one of natural earth categories : 'cultural', 'physical', 'raster'
full_url	whether to return just the filename (default) or the full URL needed for download

Details

Note that the filename of the requested object will be returned if 'load = FALSE'.

Value

string

See Also

[ne_load](#), pre-downloaded data are available using [ne_countries](#), [ne_states](#). Other geographic data are available in the raster package : [getData](#).

Examples

```
ne_name <- ne_file_name(scale = 110, type = "countries")
ne_url <- ne_file_name(scale = 110, type = "countries", full_url = TRUE)
```

ne_find_vector_data	<i>Return a dataframe of available vector layers on Natural Earth</i>
---------------------	---

Description

Checks the Natural Earth Github repository for current vector layers and provides the file name required in the type argument of `ne_download`.

Usage

```
ne_find_vector_data(  
  scale = 110,  
  category = c("cultural", "physical"),  
  getmeta = FALSE  
)
```

Arguments

scale	The scale of map to return, one of '110', '50', '10' or 'small', 'medium', 'large'.
category	one of natural earth categories : 'cultural', 'physical'
getmeta	whether to get url of the metadata for each layer

Details

Note that the filename of the requested object will be returned if 'load = FALSE'.

Value

dataframe with two variables: layer and metadata

See Also

[ne_load](#), pre-downloaded data are available using [ne_countries](#), [ne_states](#). Other geographic data are available in the raster package : [getData](#).

Examples

```
## Not run:  
ne_find_vector_data(scale = 10, category = "physical")  
  
## End(Not run)
```

ne_load	<i>load a Natural Earth vector that has already been downloaded to R using ne_download</i>
---------	--

Description

returns loaded data as a spatial object.

Usage

```
ne_load(
  scale = 110,
  type = "countries",
  category = c("cultural", "physical", "raster"),
  destdir = tempdir(),
  file_name = NULL,
  returnclass = c("sf", "sv")
)
```

Arguments

scale	The scale of map to return, one of '110', '50', '10' or 'small', 'medium', 'large'.
type	type of natural earth file one of 'countries', 'map_units', 'map_subunits', 'sovereignty', 'states' OR the portion of any natural earth vector url after the scale and before the . e.g. for 'ne_50m_urban_areas.zip' this would be 'urban_areas' OR the raster filename e.g. for 'MSR_50M.zip' this would be 'MSR_50M'
category	one of natural earth categories : 'cultural', 'physical', 'raster'
destdir	folder to load files from, default=tempdir()
file_name	OPTIONAL name of file (excluding path) instead of natural earth attributes
returnclass	A string determining the spatial object to return. Either "sf" for for simple feature (from 'sf', the default) or "sv" for a 'SpatVector' (from 'terra').

Details

Note that the filename of the requested object will be returned if 'load = FALSE'.

Value

An object of class 'sf' for simple feature (from 'sf', the default) or 'SpatVector' (from 'terra').

See Also

[ne_download](#)

Examples

```
## Not run:
# download followed by load from tempdir() works in same R session
spdf_world <- ne_download(scale = 110, type = "countries")
spdf_world2 <- ne_load(scale = 110, type = "countries")

# download followed by load from specified directory works between R sessions
spdf_world <- ne_download(scale = 110, type = "countries", destdir = getwd())
spdf_world2 <- ne_load(scale = 110, type = "countries", destdir = getwd())

# for raster download & load
rst <- ne_download(scale = 50, type = "OB_50M", category = "raster", destdir = getwd())

# load after having downloaded
rst <- ne_load(scale = 50, type = "OB_50M", category = "raster", destdir = getwd())

# plot
library(terra)
plot(rst)
# end dontrun

## End(Not run)
```

ne_states

Get natural earth world state (admin level 1) polygons

Description

returns state polygons (administrative level 1) for specified countries

Usage

```
ne_states(
  country = NULL,
  geounit = NULL,
  iso_a2 = NULL,
  spat_object = NULL,
  returnclass = c("sf", "sv")
)
```

Arguments

country	a character vector of country names.
geounit	a character vector of geounit names.
iso_a2	a character vector of iso_a2 country codes
spat_object	an optional alternative states map
returnclass	A string determining the spatial object to return. Either "sf" for for simple feature (from 'sf', the default) or "sv" for a 'SpatVector' (from 'terra').

Details

Note that the filename of the requested object will be returned if 'load = FALSE'.

Value

An object of class 'sf' for simple feature (from 'sf', the default) or 'SpatVector' (from 'terra').

See Also

[ne_load](#), pre-downloaded data are available using [ne_countries](#), [ne_states](#). Other geographic data are available in the raster package : [getData](#).

Examples

```
# comparing using country and geounit to filter
if (requireNamespace("rnaturalearthhires")) {
  spdf_france_country <- ne_states(country = "france")
  spdf_france_geounit <- ne_states(geounit = "france")

  plot(spdf_france_country)
  plot(spdf_france_geounit)

  plot(ne_states(country = "united kingdom"))
  plot(ne_states(geounit = "england"))
}
```

Index

* datasets

- countries, [5](#)
- df_layers_cultural, [6](#)
- df_layers_physical, [6](#)

- check_data_exist, [2](#)
- check_rnaturalearthdata, [3](#)
- check_rnaturalearth hires, [3](#)
- check_scale, [4](#)
- convert_spatial_class, [4](#)
- countries, [5](#)
- countries110 (countries), [5](#)

- df_layers_cultural, [6](#)
- df_layers_physical, [6](#)

- get_data, [7](#)
- getData, [3](#), [5](#), [7](#), [9](#), [10](#), [12–14](#), [17](#)

- install_rnaturalearthdata, [8](#)
- install_rnaturalearth hires, [8](#)

- ne_admin0 (ne_countries), [10](#)
- ne_admin1 (ne_states), [16](#)
- ne_coastline, [9](#)
- ne_countries, [3](#), [5](#), [7](#), [9](#), [10](#), [10](#), [12–14](#), [17](#)
- ne_download, [11](#), [15](#)
- ne_file_name, [13](#)
- ne_find_vector_data, [14](#)
- ne_load, [3–5](#), [7](#), [9–14](#), [15](#), [17](#)
- ne_states, [3](#), [5](#), [7](#), [9](#), [10](#), [12–14](#), [16](#), [17](#)