

Package: roblog (via r-universe)

July 12, 2024

Type Package

Title rOpenSci's blog guidance

Version 0.1.0

Description It provides templates for roweb2 blogging and help for a GitHub forking workflow.

License MIT + file LICENSE

URL <https://docs.ropensci.org/roblog/>,
<https://github.com/ropenscilabs/roblog>

BugReports <https://github.com/ropenscilabs/roblog/issues>

Imports base64enc, clipr, commonmark, crul (>= 0.9.1.9992), dplyr, fs, gh, glue, magrittr, purrr, rlang, rstudioapi, stringr, textutils, tibble, urltools, usethis, whoami, xml2, xmlparsedata

Suggests details, gluedown, knitr, rmarkdown, testthat (>= 3.0.0)

VignetteBuilder knitr

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.1

Config/testthat/edition 3

Repository <https://ropensci.r-universe.dev>

RemoteUrl <https://github.com/ropensci-org/roblog>

RemoteRef main

RemoteSha cc3866e831c5fb5f5494d1ba9be67a4c5aa5a336

Contents

create_newsletter_content	2
ro_blog_post_author	2
ro_check_urls	3
ro_lint_md	3

`create_newsletter_content`*Create newsletter content for Sendgrid*

Description

Create newsletter content for Sendgrid

Usage

```
create_newsletter_content()
```

Value

Text copied to clipboard to be pasted into Sendgrid

`ro_blog_post_author` *Create a new rOpenSci author file*

Description

Create a new author file, in RStudio.

Usage

```
ro_blog_post_author()
```

Details

Call it via the add-in or directly or get the [templates online](#).

In any case, an internet connection is required as templates are downloaded fresh from their source

`ro_blog_post_author()` creates Markdown files, RStudio might warn you against saving them as ".md" but ignore that.

ro_check_urls	<i>Check URLs in Markdown post</i>
---------------	------------------------------------

Description

Check URLs in Markdown post

Usage

```
ro_check_urls(path = NULL)
```

Arguments

path	Path to the Markdown post (not source Rmd!) – if NULL, and in RStudio, roblog will default to the md resulting from the active Rmd.
------	---

Examples

```
## Not run:  
path <- system.file(file.path("examples", "bad-no-alt.md"),  
  package = "roblog"  
)  
ro_check_urls(path)  
  
## End(Not run)
```

ro_lint_md	<i>Lint Markdown post for rOpenSci blog</i>
------------	---

Description

Lint Markdown post for rOpenSci blog

Usage

```
ro_lint_md(path = NULL)
```

Arguments

path	Path to the Markdown post (not source Rmd!) – if NULL, and in RStudio, roblog will default to the md resulting from the active Rmd.
------	---

Examples

```
## Not run:  
path <- system.file(  
  file.path("examples", "bad-no-alt.md"),  
  package = "roblog"  
)  
  
## End(Not run)
```

Index

`create_newsletter_content`, [2](#)

`ro_blog_post_author`, [2](#)

`ro_check_urls`, [3](#)

`ro_lint_md`, [3](#)