

# Package: taxadb (via r-universe)

March 14, 2025

**Version** 0.2.1.99

**Title** A High-Performance Local Taxonomic Database Interface

**Description** Creates a local database of many commonly used taxonomic authorities and provides functions that can quickly query this data.

**License** MIT + file LICENSE

**Encoding** UTF-8

**ByteCompile** true

**Depends** R (>= 4.0)

**Imports** DBI, duckdb, tibble, dplyr, dbplyr, rlang, magrittr, stringi, contentid, memoise

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.2.3

**Suggests** spelling, testthat, covr, knitr, rmarkdown, purrr, crayon, RSQLite

**Language** en-US

**VignetteBuilder** knitr

**URL** <<https://docs.ropensci.org/taxadb/>>,  
<<https://github.com/ropensci/taxadb>>

**BugReports** <https://github.com/ropensci/taxadb/issues>

**Config/pak/sysreqs** make libicu-dev libssl-dev xz-utils

**Repository** <https://ropensci.r-universe.dev>

**RemoteUrl** <https://github.com/ropensci/taxadb>

**RemoteRef** master

**RemoteSha** 6c2023d7e11d9a189603bd98d4514d0f85891816

## Contents

clean_names . . . . .	2
common_contains . . . . .	3
common_starts_with . . . . .	4
filter_by . . . . .	5
filter_common . . . . .	6
filter_id . . . . .	7
filter_name . . . . .	9
filter_rank . . . . .	10
fuzzy_filter . . . . .	11
get_ids . . . . .	12
get_names . . . . .	14
name_contains . . . . .	15
name_starts_with . . . . .	16
taxadb_dir . . . . .	17
taxa_tbl . . . . .	17
td_connect . . . . .	18
td_create . . . . .	19
td_disconnect . . . . .	21
tl_import . . . . .	21
<b>Index</b>	<b>23</b>

---

clean_names	<i>Clean taxonomic names</i>
-------------	------------------------------

---

## Description

A utility to sanitize taxonomic names to increase probability of resolving names.

## Usage

```
clean_names(
  names,
  fix_delim = TRUE,
  binomial_only = TRUE,
  remove_sp = TRUE,
  ascii_only = TRUE,
  lowercase = TRUE,
  remove_punc = FALSE
)
```

**Arguments**

names	a character vector of taxonomic names (usually species names)
fix_delim	Should we replace separators ., _, - with spaces? e.g. 'Homo.sapiens' becomes 'Homo sapiens'. logical, default TRUE.
binomial_only	Attempt to prune name to a binomial name, e.g. Genus and species (specific epithet), e.g. Homo sapiens sapiens becomes Homo sapiens. logical, default <b>TRUE</b> .
remove_sp	Should we drop unspecified species epithet designations? e.g. Homo sp. becomes Homo (thus only matching against genus level ids). logical, default <b>TRUE</b> .
ascii_only	should we coerce strings to ascii characters? (see <a href="#">stringi::stri_trans_general()</a> )
lowercase	should names be coerced to lower-case to provide case-insensitive matching?
remove_punc	replace all punctuation but apostrophes with a space, remove apostrophes

**Details**

Current implementation is limited to handling a few common cases. Additional extensions may be added later. A goal of the `clean_names` function is that any modification rule of the name strings be precise, atomic, and toggle-able, rather than relying on clever but more opaque rules and arbitrary scores. This utility should always be used with care, as indiscriminate modification of names may result in successful but inaccurate name matching. A good pattern is to only apply this function to the subset of names that cannot be directly matched.

**Examples**

```
clean_names(c("Homo sapiens sapiens", "Homo.sapiens", "Homo sp."))
```

---

common_contains	<i>common name starts with</i>
-----------------	--------------------------------

---

**Description**

common name starts with

**Usage**

```
common_contains(
  name,
  provider = getOption("taxadb_default_provider", "itis"),
  version = latest_version(),
  db = td_connect(),
  ignore_case = TRUE
)
```

**Arguments**

name	vector of names (scientific or common, see by) to be matched against.
provider	from which provider should the hierarchy be returned? Default is 'itis', which can also be configured using options(default_taxadb_provider=...). See [td_create] for a list of recognized providers.
version	Which version of the taxadb provider database should we use? defaults to latest. See <a href="#">tl_import</a> for details.
db	a connection to the taxadb database. See details.
ignore_case	should we ignore case (capitalization) in matching names? Can be significantly slower to run.

**Examples**

```
common_contains("monkey")
```

---

```
common_starts_with    common name starts with
```

---

**Description**

common name starts with

**Usage**

```
common_starts_with(
  name,
  provider = getOption("taxadb_default_provider", "itis"),
  version = latest_version(),
  db = td_connect(),
  ignore_case = TRUE
)
```

**Arguments**

name	vector of names (scientific or common, see by) to be matched against.
provider	from which provider should the hierarchy be returned? Default is 'itis', which can also be configured using options(default_taxadb_provider=...). See [td_create] for a list of recognized providers.
version	Which version of the taxadb provider database should we use? defaults to latest. See <a href="#">tl_import</a> for details.
db	a connection to the taxadb database. See details.
ignore_case	should we ignore case (capitalization) in matching names? Can be significantly slower to run.

**Examples**

```
common_starts_with("monkey")
```

---

filter_by	<i>Creates a data frame with column name given by by, and values given by the vector x, and then uses this table to do a filtering join, joining on the by column to return all rows matching the x values (scientificNames, taxonIDs, etc).</i>
-----------	--

---

**Description**

Creates a data frame with column name given by by, and values given by the vector x, and then uses this table to do a filtering join, joining on the by column to return all rows matching the x values (scientificNames, taxonIDs, etc).

**Usage**

```
filter_by(
  x,
  by,
  provider = getOption("taxadb_default_provider", "itis"),
  schema = c("dwc", "common"),
  version = latest_version(),
  collect = TRUE,
  db = td_connect(),
  ignore_case = FALSE
)
```

**Arguments**

x	a vector of values to filter on
by	a column name in the taxa_tbl (following Darwin Core Schema terms). The filtering join is executed with this column as the joining variable.
provider	from which provider should the hierarchy be returned? Default is 'itis', which can also be configured using options(default_taxadb_provider=...). See [td_create] for a list of recognized providers.
schema	One of "dwc" (for Darwin Core data) or "common" (for the Common names table.)
version	Which version of the taxadb provider database should we use? defaults to latest. See <a href="#">tl_import</a> for details.
collect	logical, default TRUE. Should we return an in-memory data.frame (default, usually the most convenient), or a reference to lazy-eval table on disk (useful for very large tables on which we may first perform subsequent filtering operations.)

db a connection to the taxadb database. See details.

ignore\_case should we ignore case (capitalization) in matching names? Can be significantly slower to run.

### Value

a data.frame in the Darwin Core tabular format containing the matching taxonomic entities.

### See Also

Other filter\_by: [filter\\_common\(\)](#), [filter\\_id\(\)](#), [filter\\_name\(\)](#), [filter\\_rank\(\)](#)

### Examples

```
sp <- c("Trochalopteron henrici gucenense",
       "Trochalopteron elliotii")
filter_by(sp, "scientificName")

filter_by(c("ITIS:1077358", "ITIS:175089"), "taxonID")

filter_by("Aves", "class")
```

---

filter\_common

*Look up taxonomic information by common name*

---

### Description

Look up taxonomic information by common name

### Usage

```
filter_common(
  name,
  provider = getOption("taxadb_default_provider", "itis"),
  version = latest_version(),
  collect = TRUE,
  ignore_case = TRUE,
  db = td_connect()
)
```

**Arguments**

name	a character vector of common (vernacular English) names, e.g. "Humans"
provider	from which provider should the hierarchy be returned? Default is 'itis', which can also be configured using <code>options(default_taxadb_provider=...)</code> . See <code>[td_create]</code> for a list of recognized providers.
version	Which version of the taxadb provider database should we use? defaults to latest. See <a href="#">tl_import</a> for details.
collect	logical, default TRUE. Should we return an in-memory data.frame (default, usually the most convenient), or a reference to lazy-eval table on disk (useful for very large tables on which we may first perform subsequent filtering operations.)
ignore_case	should we ignore case (capitalization) in matching names? Can be significantly slower to run.
db	a connection to the taxadb database. See details.

**Value**

a data.frame in the Darwin Core tabular format containing the matching taxonomic entities.

**See Also**

Other filter\_by: [filter\\_by\(\)](#), [filter\\_id\(\)](#), [filter\\_name\(\)](#), [filter\\_rank\(\)](#)

**Examples**

```
filter_common("Pied Tamarin")
```

---

filter\_id

*Return a taxonomic table matching the requested ids*

---

**Description**

Return a taxonomic table matching the requested ids

**Usage**

```
filter_id(
  id,
  provider = getOption("taxadb_default_provider", "itis"),
  type = c("taxonID", "acceptedNameUsageID"),
  version = latest_version(),
```

```

    collect = TRUE,
    db = td_connect()
)

```

### Arguments

id	taxonomic id, in prefix format
provider	from which provider should the hierarchy be returned? Default is 'itis', which can also be configured using <code>options(default_taxadb_provider=...)</code> . See <code>[td_create]</code> for a list of recognized providers.
type	id type. Can be <code>taxonID</code> or <code>acceptedNameUsageID</code> , see details.
version	Which version of the taxadb provider database should we use? defaults to latest. See <a href="#">tl_import</a> for details.
collect	logical, default TRUE. Should we return an in-memory data.frame (default, usually the most convenient), or a reference to lazy-eval table on disk (useful for very large tables on which we may first perform subsequent filtering operations.)
db	a connection to the taxadb database. See details.

### Details

Use `type="acceptedNameUsageID"` to return all rows for which this ID is the accepted ID, including both synonyms and accepted names (since both all synonyms of a name share the same `acceptedNameUsageID`.) Use `taxonID` (default) to only return those rows for which the Scientific name corresponds to the `taxonID`.

Some providers (e.g. ITIS) assign `taxonIDs` to synonyms, most others only assign IDs to accepted names. In the latter case, this means requesting `taxonID` will only match accepted names, while requesting matches to the `acceptedNameUsageID` will also return any known synonyms. See examples.

### Value

a data.frame with id and name of all matching species

### See Also

Other filter\_by: [filter\\_by\(\)](#), [filter\\_common\(\)](#), [filter\\_name\(\)](#), [filter\\_rank\(\)](#)

### Examples

```

filter_id(c("ITIS:1077358", "ITIS:175089"))
filter_id("ITIS:1077358", type="acceptedNameUsageID")

```



---

filter_name	<i>Look up taxonomic information by scientific name</i>
-------------	---

---

### Description

Look up taxonomic information by scientific name

### Usage

```
filter_name(
  name,
  provider = getOption("taxadb_default_provider", "itis"),
  version = latest_version(),
  collect = TRUE,
  ignore_case = FALSE,
  db = td_connect()
)
```

### Arguments

name	a character vector of scientific names, e.g. "Homo sapiens"
provider	from which provider should the hierarchy be returned? Default is 'itis', which can also be configured using <code>options(default_taxadb_provider=...)</code> . See <code>[td_create]</code> for a list of recognized providers.
version	Which version of the taxadb provider database should we use? defaults to latest. See <a href="#">tl_import</a> for details.
collect	logical, default TRUE. Should we return an in-memory data.frame (default, usually the most convenient), or a reference to lazy-eval table on disk (useful for very large tables on which we may first perform subsequent filtering operations.)
ignore_case	should we ignore case (capitalization) in matching names? Can be significantly slower to run.
db	a connection to the taxadb database. See details.

### Details

Most but not all authorities can match against both species level and higher-level (or lower, e.g. subspecies or variety) taxonomic names. The rank level is indicated by `taxonRank` column.

Most authorities include both known synonyms and accepted names in the `scientificName` column, (with the status indicated by `taxonomicStatus`). This is convenient, as users will typically not know if the names they have are synonyms or accepted names, but will want to get the match to the accepted name and accepted ID in either case.

### Value

a data.frame in the Darwin Core tabular format containing the matching taxonomic entities.

**See Also**

Other filter\_by: [filter\\_by\(\)](#), [filter\\_common\(\)](#), [filter\\_id\(\)](#), [filter\\_rank\(\)](#)

**Examples**

```
sp <- c("Trochalopteron henrici gucenense",
       "Trochalopteron elliotii")
filter_name(sp)
```

---

filter_rank	<i>Get all members (descendants) of a given rank level</i>
-------------	--

---

**Description**

Get all members (descendants) of a given rank level

**Usage**

```
filter_rank(
  name,
  rank,
  provider = getOption("taxadb_default_provider", "itis"),
  version = latest_version(),
  collect = TRUE,
  ignore_case = TRUE,
  db = td_connect()
)
```

**Arguments**

name	taxonomic scientific name (e.g. "Aves")
rank	taxonomic rank name. (e.g. "class")
provider	from which provider should the hierarchy be returned? Default is 'itis', which can also be configured using <code>options(default_taxadb_provider=...)</code> . See <code>[td_create]</code> for a list of recognized providers.
version	Which version of the taxadb provider database should we use? defaults to latest. See <a href="#">tl_import</a> for details.
collect	logical, default TRUE. Should we return an in-memory data.frame (default, usually the most convenient), or a reference to lazy-eval table on disk (useful for very large tables on which we may first perform subsequent filtering operations.)
ignore_case	should we ignore case (capitalization) in matching names? Can be significantly slower to run.
db	a connection to the taxadb database. See details.

**Value**

a data.frame in the Darwin Core tabular format containing the matching taxonomic entities.

**See Also**

Other filter\_by: [filter\\_by\(\)](#), [filter\\_common\(\)](#), [filter\\_id\(\)](#), [filter\\_name\(\)](#)

**Examples**

```
filter_rank("Aves", "class")
```

---

fuzzy\_filter

---

*Match names that start or contain a specified text string*


---

**Description**

Match names that start or contain a specified text string

**Usage**

```
fuzzy_filter(
  name,
  by = c("scientificName", "vernacularName"),
  provider = getOption("taxadb_default_provider", "itis"),
  match = c("contains", "starts_with"),
  version = latest_version(),
  db = td_connect(),
  ignore_case = TRUE,
  collect = TRUE
)
```

**Arguments**

name	vector of names (scientific or common, see by) to be matched against.
by	a column name in the taxa_tbl (following Darwin Core Schema terms). The filtering join is executed with this column as the joining variable.
provider	from which provider should the hierarchy be returned? Default is 'itis', which can also be configured using options(default_taxadb_provider=...). See [td_create] for a list of recognized providers.
match	should we match by names starting with the term or containing the term anywhere in the name?

version	Which version of the taxadb provider database should we use? defaults to latest. See <a href="#">tl_import</a> for details.
db	a connection to the taxadb database. See details.
ignore_case	should we ignore case (capitalization) in matching names? Can be significantly slower to run.
collect	logical, default TRUE. Should we return an in-memory data.frame (default, usually the most convenient), or a reference to lazy-eval table on disk (useful for very large tables on which we may first perform subsequent filtering operations.)

### Details

Note that fuzzy filter will be fast with an single or small number of names, but will be slower if given a very large vector of names to match, as unlike other `filter_` commands, fuzzy matching requires separate SQL calls for each name. As fuzzy matches should all be confirmed manually in any event, e.g. not every common name containing "monkey" belongs to a primate species.

This method utilizes the database operation `%like%` to filter tables without loading into memory. Note that this does not support the use of regular expressions at this time.

### Examples

```
## match any common name containing:
name <- c("woodpecker", "monkey")
fuzzy_filter(name, "vernacularName")

## match scientific name
fuzzy_filter("Chera", "scientificName",
             match = "starts_with")
```

---

get\_ids

*get\_ids*

---

### Description

A drop-in replacement for `[taxize::get_ids()]`

### Usage

```
get_ids(
  names,
  provider = getOption("taxadb_default_provider", "itis"),
  format = c("prefix", "bare", "uri"),
  version = latest_version(),
  taxadb_db = td_connect(),
```

```

    ignore_case = FALSE,
    warn = TRUE,
    db = NULL,
    ...
)

```

### Arguments

names	a list of scientific names (which may include higher-order ranks in most authorities).
provider	abbreviation code for the provider. See details.
format	Format for the returned identifier, one of <ul style="list-style-type: none"> <li>• prefix (e.g. NCBI:9606, the default), or</li> <li>• bare (e.g. 9606, used in <code>taxize::get_ids()</code>),</li> <li>• uri (e.g. <code>http://ncbi.nlm.nih.gov/taxonomy/9606</code>).</li> </ul>
version	Which version of the taxadb provider database should we use? defaults to latest. see [ <code>available_releases()</code> ] for details.
taxadb_db	Connection to from [ <code>td_connect()</code> ].
ignore_case	should we ignore case (capitalization) in matching names? default is TRUE.
warn	should we display warnings on NAs resulting from multiply-resolved matches? (Unlike unmatched names, these NAs can usually be resolved manually via <code>filter_id()</code> )
db	previous name for provider argument, now deprecated
...	additional arguments (currently ignored)

### Details

Note that some taxize authorities: `nbn`, `tropicos`, and `eol`, are not recognized by taxadb and will throw an error here. Meanwhile, taxadb recognizes several authorities not known to [`taxize::get_ids()`]. Both include `itis`, `ncbi`, `col`, and `gbif`.

Like all taxadb functions, this function will run fastest if a local copy of the provider is installed in advance using [`td_create()`].

### Value

a vector of IDs, of the same length as the input names Any unmatched names or multiply-matched names will return as `NAs`. To resolve multi-matched names, use [`filter_name()`] instead to return a table with a separate row for each separate match of the input name.

### See Also

`filter_name`

Other get: `get_names()`

## Examples

```
get_ids("Midas bicolor")
get_ids(c("Midas bicolor", "Homo sapiens"), format = "prefix")
get_ids("Midas bicolor", format = "uri")
```

---

get\_names

*get\_names*

---

## Description

Translate identifiers into scientific names

## Usage

```
get_names(
  id,
  provider = getOption("taxadb_default_provider", "itis"),
  version = latest_version(),
  format = c("guess", "prefix", "bare", "uri"),
  taxadb_db = td_connect(),
  db = NULL
)
```

## Arguments

id	a list of taxonomic identifiers.
provider	abbreviation code for the provider. See details.
version	Which version of the taxadb provider database should we use? defaults to latest. see [available_releases()] for details.
format	Format for the returned identifier, one of <ul style="list-style-type: none"> <li>• prefix (e.g. NCBI:9606, the default), or</li> <li>• bare (e.g. 9606, used in taxize::get_ids()),</li> <li>• uri (e.g. http://ncbi.nlm.nih.gov/taxonomy/9606).</li> </ul>
taxadb_db	Connection to from [td_connect()].
db	previous name for provider argument, now deprecated

**Details**

Like all taxadb functions, this function will run fastest if a local copy of the provider is installed in advance using `[td_create()]`.

**Value**

a vector of names, of the same length as the input ids. Any unmatched IDs will return as [NAs](#).

**See Also**

Other get: [get\\_ids\(\)](#)

**Examples**

```
get_names(c("ITIS:1025094", "ITIS:1025103"), format = "prefix")
```

---

name_contains	<i>return all taxa in which scientific name contains the text provided</i>
---------------	--

---

**Description**

return all taxa in which scientific name contains the text provided

**Usage**

```
name_contains(
  name,
  provider = getOption("taxadb_default_provider", "itis"),
  version = latest_version(),
  db = td_connect(),
  ignore_case = TRUE
)
```

**Arguments**

name	vector of names (scientific or common, see <code>by</code> ) to be matched against.
provider	from which provider should the hierarchy be returned? Default is 'itis', which can also be configured using <code>options(default_taxadb_provider=...)</code> . See <code>[td_create]</code> for a list of recognized providers.
version	Which version of the taxadb provider database should we use? defaults to latest. See <a href="#">tl_import</a> for details.

db a connection to the taxadb database. See details.

ignore\_case should we ignore case (capitalization) in matching names? Can be significantly slower to run.

### Examples

```
name_contains("Chera")
```

---

name_starts_with	<i>scientific name starts with</i>
------------------	------------------------------------

---

### Description

scientific name starts with

### Usage

```
name_starts_with(
  name,
  provider = getOption("taxadb_default_provider", "itis"),
  version = latest_version(),
  db = td_connect(),
  ignore_case = TRUE
)
```

### Arguments

name vector of names (scientific or common, see `by`) to be matched against.

provider from which provider should the hierarchy be returned? Default is 'itis', which can also be configured using `options(default_taxadb_provider=...)`. See `[td_create]` for a list of recognized providers.

version Which version of the taxadb provider database should we use? defaults to latest. See [tl\\_import](#) for details.

db a connection to the taxadb database. See details.

ignore\_case should we ignore case (capitalization) in matching names? Can be significantly slower to run.

### Examples

```
name_starts_with("Chera")
```



---

taxadb_dir	<i>Show the taxadb directory</i>
------------	----------------------------------

---

**Description**

Show the taxadb directory

**Usage**

```
taxadb_dir()
```

**Details**

NOTE: after upgrading duckdb, a user may need to delete any existing databases created with the previous version. An efficient way to do so is `unlink(taxadb::taxadb_dir(), TRUE)`.

**Examples**

```
## show the directory
taxadb_dir()
## Purge the local db
unlink(taxadb::taxadb_dir(), TRUE)
```

---

taxa_tbl	<i>Return a reference to a given table in the taxadb database</i>
----------	---

---

**Description**

Return a reference to a given table in the taxadb database

**Usage**

```
taxa_tbl(
  provider = getOption("taxadb_default_provider", "itis"),
  schema = c("dwc", "common"),
  version = latest_version(),
  db = td_connect()
)
```

**Arguments**

provider	from which provider should the hierarchy be returned? Default is 'itis', which can also be configured using options(default_taxadb_provider=...). See [td_create] for a list of recognized providers.
schema	One of "dwc" (for Darwin Core data) or "common" (for the Common names table.)
version	Which version of the taxadb provider database should we use? defaults to latest. See <a href="#">tl_import</a> for details.
db	a connection to the taxadb database. See details.

**Examples**

```
## default schema is the dwc table
taxa_tbl()

## common names table
taxa_tbl(schema = "common")
```

---

td_connect	<i>Connect to the taxadb database</i>
------------	---------------------------------------

---

**Description**

Connect to the taxadb database

**Usage**

```
td_connect(dbdir = NULL, driver = NULL, read_only = NULL)
```

**Arguments**

dbdir	Path to the database. no longer needed
driver	deprecated, ignored. driver will always be duckdb.
read_only	deprecated, driver is always read-only.

**Details**

This function provides a default database connection for `taxadb`. Note that you can use `taxadb` with any DBI-compatible database connection by passing the connection object directly to `taxadb` functions using the `db` argument. `td_connect()` exists only to provide reasonable automatic defaults based on what is available on your system.

For performance reasons, this function will also cache and restore the existing database connection, making repeated calls to `td_connect()` much faster and more failsafe than repeated calls to [DBI::dbConnect](#)

**Value**

Returns a DBI connection to the default duckdb database

**Examples**

```
## OPTIONAL: you can first set an alternative home location,
## such as a temporary directory:
Sys.setenv(TAXADB_HOME=file.path(tempdir(), "taxadb"))

## Connect to the database:
db <- td_connect()
```

---

 td\_create | *create a local taxonomic database* |

---

**Description**

create a local taxonomic database

**Usage**

```
td_create(
  provider = getOption("taxadb_default_provider", "itis"),
  schema = c("dwc", "common"),
  version = latest_version(),
  overwrite = NULL,
  lines = NULL,
  dbdir = NULL,
  db = td_connect()
)
```

## Arguments

provider	a list (character vector) of provider(s) to be included in the database. By default, will install <code>itis</code> . See details for a list of recognized provider. available provider automatically.
schema	One of "dwc" (for Darwin Core data) or "common" (for the Common names table.)
version	Which version of the taxadb provider database should we use? defaults to latest. See <code>tl_import</code> for details.
overwrite	Should we overwrite existing tables? Default is TRUE. Change to "ask" for interactive interface, or TRUE to force overwrite (i.e. updating a local database upon new release.)
lines	number of lines that can be safely read in to memory at once. Leave at default or increase for faster importing if you have plenty of spare RAM.
dbdir	a location on your computer where the database should be installed. Defaults to user data directory given by <code>[tools::R_user_dir()]</code> .
db	connection to a database. By default, taxadb will set up its own fast database connection.

## Details

Authorities currently recognized by taxadb are:

- `itis`: Integrated Taxonomic Information System, <https://www.itis.gov>
- `ncbi`: National Center for Biotechnology Information, <https://www.ncbi.nlm.nih.gov/taxonomy>
- `col`: Catalogue of Life, <http://www.catalogueoflife.org/>
- `gbif`: Global Biodiversity Information Facility, <https://www.gbif.org/>
- `ott`: OpenTree Taxonomy: <https://github.com/OpenTreeOfLife/reference-taxonomy>
- `iucn`: IUCN Red List, <https://iucnredlist.org>
- `itis_test`: a small subset of ITIS, cached locally with the package for testing purposes only

## Value

path where database has been installed (invisibly)

## Examples

```
## Install the ITIS database
td_create()

## force re-install:
td_create( overwrite = TRUE)
```

---

td_disconnect	<i>Disconnect from the taxadb database.</i>
---------------	---

---

**Description**

Disconnect from the taxadb database.

**Usage**

```
td_disconnect(db = td_connect())
```

**Arguments**

db                    database connection

**Details**

This function manually closes a connection to the taxadb database.

**Examples**

```
## Disconnect from the database:  
td_disconnect()
```

---

tl_import	<i>Import taxonomic database tables</i>
-----------	---

---

**Description**

Downloads the requested taxonomic data tables and return a local path to the data in tsv.gz format. Downloads are cached and identified by content hash so that tl\_import will not attempt to download the same file multiple times.

**Usage**

```
tl_import(  
  provider = getOption("tl_default_provider", "itis"),  
  schema = c("dwc", "common"),  
  version = latest_version(),  
  prov = prov_cache()  
)
```

**Arguments**

provider	from which provider should the hierarchy be returned? Default is 'itis', which can also be configured using options(default_taxadb_provider=...). See [td_create] for a list of recognized providers.
schema	One of "dwc" (for Darwin Core data) or "common" (for the Common names table.)
version	Which version of the taxadb provider database should we use? defaults to latest. See <a href="#">tl_import</a> for details.
prov	Address (URL) to provenance record

**Details**

tl\_import parses a schema.org record to determine the correct version to download. If offline, tl\_import will attempt to resolve against its own provenance cache. Users can also examine / parse the prov JSON-LD file directly to determine the provenance of the data products used.

**Value**

path(s) to the downloaded files in the cache

# Index

- \* **filter\_by**
  - filter\_by, 5
  - filter\_common, 6
  - filter\_id, 7
  - filter\_name, 9
  - filter\_rank, 10
- \* **get**
  - get\_ids, 12
  - get\_names, 14
- clean\_names, 2
- common\_contains, 3
- common\_starts\_with, 4
- DBI:::dbConnect, 19
- filter\_by, 5, 7, 8, 10, 11
- filter\_common, 6, 6, 8, 10, 11
- filter\_id, 6, 7, 7, 10, 11
- filter\_id(), 13
- filter\_name, 6–8, 9, 11
- filter\_rank, 6–8, 10, 10
- fuzzy\_filter, 11
- get\_ids, 12, 15
- get\_names, 13, 14
- NA, 13, 15
- name\_contains, 15
- name\_starts\_with, 16
- stringi::stri\_trans\_general(), 3
- taxa\_tbl, 17
- taxadb\_dir, 17
- td\_connect, 18
- td\_create, 19
- td\_disconnect, 21
- tl\_import, 4, 5, 7–10, 12, 15, 16, 18, 20, 21, 22
- TRUE, 3